

Amendments to the Drawings:

The attached replacement sheets of drawings includes changes to all Figures and replace the original sheets as filed.

Attachments following last page of this Amendment:

Replacement Sheet (27 pages)

Annotated Sheet Showing Change(s) (27 pages)

REMARKS

In response to the final office action dated April 27, 2007, Applicants are submitting a substitute specification that corrects minor informalities in the references numbers as well as typographical errors. Substitute drawings reflecting the reference numbers are also submitted. Independent claim 1 is being canceled without prejudice and new claims 2-28 are being submitted. Favorable consideration of the new claims is requested.

The present amendments

Minor corrections are made in the specification and drawings to clarify the reference numbers. For example, each of the reference numbers 1-17 that are shown in Figure 1 have been provided with the prefix "1" (because they are in Figure 1), thus: 1-1, 1-2, ..., 1-17. Similar changes are made in the remaining drawings. These changes are supported by the original disclosure as filed, because Applicants are merely adding prefixes to the existing numbers.

New claims 2-28 are directed to methods of creating a semantic object. These amendments are supported throughout the present disclosure, for example in the places mentioned within parentheses for respective features. For clarity, the references refer to the page and line numbers in the specification as filed (i.e., not to the substitute specification filed herewith).

Independent claim 2 recites:

2. (New) A computer-implemented method of creating a semantic object representing a target referent, the method comprising:
 - identifying a target referent; (13:19; 18:24; 20:5)
 - creating a semantic object to represent the target referent in a computer system having stored therein a plurality of semantic objects representing respective target referents, the semantic object being created using a semantic object type selected from an ontology of semantic object types; (14:17; 15:24; 32:21; 41:17; 82:10)
 - including in the created semantic object content relating to the target referent; (14:24; 20:26)

analyzing the content relative to content in at least one of the plurality of semantic objects; and (30:12; 33:12; 35:2; 64:24)

creating an association between the created semantic object and any of the at least one of the plurality of semantic objects based on the analysis. (30:11)

Dependent claim 3 recites:

3. (New) The computer-implemented method of claim 2, further comprising assigning one of multiple lifecycle stages to the created semantic object. (17:4)

Dependent claim 4 recites:

4. (New) The computer-implemented method of claim, wherein the multiple lifecycle stages include at least: a draft stage, an active stage, an inactive stage and a deleted stage, further comprising subsequently transitioning the created semantic object from one of the multiple lifecycle stages to another. (17:4)

Dependent claim 5 recites:

5. (New) The computer-implemented method of claim 2, wherein the created semantic object has multiple slots, further comprising receiving an input that defines at least one of the slots as required and at least another one of the slots as optional. (17:23)

Dependent claim 6 recites:

6. (New) The computer-implemented method of claim 5, further comprising applying, when the created semantic object is shared with a user, a default rule (i) to share the at least one required slot with the user; and (ii) not to share the at least one optional slot with the user. (17:24; 18:6)

Dependent claim 7 recites:

7. (New) The computer-implemented method of claim 5, further comprising receiving a specific designation that the at least one optional slot is to be shared, and sharing the at least one optional slot in response to the specific designation. (18:3)

Dependent claim 8 recites:

8. (New) The computer-implemented method of claim 5, further comprising:
receiving a user modification of the created semantic object that changes at least one of the multiple slots as defined in the semantic object type; and

storing the received user modification as an extension of the semantic object type.

(70:23)

Dependent claim 9 recites:

9. (New) The computer-implemented method of claim 8, further comprising:
storing multiple extensions based on user modifications; and
ranking the multiple extensions by popularity. (71:6)

Dependent claim 10 recites:

10. (New) The computer-implemented method of claim 8, further comprising:
storing multiple extensions based on user modifications; and
ranking each slot in the multiple extensions by popularity. (71:6)

Dependent claim 11 recites:

11. (New) The computer-implemented method of claim 2, further comprising
exchanging information about the ontology using the semantic object. (19:6)

Dependent claim 12 recites:

12. (New) The computer-implemented method of claim 2, further comprising
extracting at least part of the content from the target referent before inclusion in the
created semantic object. (20:7)

Dependent claim 13 recites:

13. (New) The computer-implemented method of claim 12, further comprising
subsequently determining that the referent target has been revised and updating the
created semantic object using the revision. (20:20)

Dependent claim 14 recites:

14. (New) The computer-implemented method of claim 12, wherein the extraction is
part of a data mining performed on selected resources. (20:5)

Dependent claim 15 recites:

15. (New) The computer-implemented method of claim 2, further comprising sharing
the created semantic object with a user and updating the created semantic object to reflect
a change made by the user. (20:1)

Dependent claim 16 recites:

16. (New) The computer-implemented method of claim 2, wherein the semantic object is created essentially simultaneously with creation of the referent target. (20:9)
Dependent claim 17 recites:

17. (New) The computer-implemented method of claim 14, wherein at least one of the creation of the semantic object and modification of the created semantic object is triggered by any event selected from the group consisting of:

- saving a document or data item;
- creating a document or data item;
- opening or viewing a document or data item;
- modifying a document or data item;
- transmitting a document or data item;
- receiving a document or data item;
- deleting a document or data item; and
- integrating documents or data items with existing file servers, databases or search

engines. (20:15-25)

Dependent claim 18 recites:

18. (New) The computer-implemented method of claim 2, wherein the created semantic object can be relocated in the computer system, further comprising ensuring that the created semantic object and the referent target are not separated. (25:10)

Dependent claim 19 recites:

19. (New) The computer-implemented method of claim 18, further comprising:
maintaining a table of mappings between the plurality of semantic objects and the respective target referents; and
further providing a daemon that watches for changes and updates the association table accordingly. (26:4)

Dependent claim 20 recites:

20. (New) The computer-implemented method of claim 2, further comprising:
creating a linking semantic object between the created semantic object and at least another one of the plurality of semantic objects; and

assigning a confidence value to the link that represents an estimation of the linking semantic object's correctness. (31:16)

Dependent claim 21 recites:

21. (New) The computer-implemented method of claim 2, further comprising:
creating a linking semantic object between the created semantic object and at least another one of the plurality of semantic objects; and
folding the created linking semantic object into at least one of the created semantic object and the at least another one of the plurality of semantic objects. (32:15)

Dependent claim 22 recites:

22. (New) The computer-implemented method of claim 2, further comprising embedding the created semantic object in the referent target. (25:23)

Dependent claim 23 recites:

23. (New) The computer-implemented method of claim 2, further comprising creating a link between the created semantic object and any of the at least one of the plurality of semantic objects, the created link having a type specified by a rule. (37:13)

Dependent claim 24 recites:

24. (New) The computer-implemented method of claim 2, further comprising:
receiving a query created by a user;
creating a view that stores the received query;
creating a view semantic object that represents the view; and
sharing the created view semantic object with at least another user in the computer system. (46:4)

Dependent claim 25 recites:

25. (New) The computer-implemented method of claim 2, wherein the semantic object is created in a process of matching offers and requests, the offers represented by offer objects and the requests represented by request objects, and wherein the offer objects and the request objects are semantic object that include (i) metadata defining particulars of the offers and the requests, and (ii) payload data. (59:19)

Dependent claim 26 recites:

26. (New) The computer-implemented method of claim 25, wherein metadata is maintained using an approach selected from:

storing offer or request metadata in metatags in the created semantic object;

creating a separate semantic object and storing the offer or request metadata in the created separate semantic object, and wrapping the created semantic object using the created separate semantic object; and

creating a separate semantic object and storing the offer or request metadata in the created separate semantic object, and creating a reference pointer between the created semantic object and the created separate semantic object. (59:11; 59:13; 59:14:59:15)

Dependent claim 27 recites:

27. (New) The computer-implemented method of claim 25, further comprising:

test posting the created semantic object to provide an estimate of a number of matches; and

providing for revision of the created semantic object based on the test posting.

(60:20)

Dependent claim 28 recites:

28. (New) The computer-implemented method of claim 27, wherein a user provides example semantic objects that are test posted and evaluated, further comprising generating an optimized semantic card specification based on the test posting. (60:23)
No new matter is added

Rejection under section 101

Claim 1 was rejected under § 101 as allegedly directed to non-statutory subject matter. This rejection is rendered moot by the cancellation of claim 1. However, Applicants are not conceding that the rejection has merit. Moreover, Applicants submits that new claims 2-28 are directed to methods as recited in their preambles and are therefore statutory.

Rejection under section 103(a)

Claim 1 was rejected under § 103(a) as allegedly unpatentable over U.S. 6,513,059 (Gupta) in view of U.S. 5,809,297 (Kroenke). This rejection is rendered moot by the

cancellation of claim 1. However, Applicants are not conceding that the rejection has merit. Moreover, Applicants submits that new claims 2-28 are not rendered unpatentable by Gupta or Kroenke taken separately or in combination.

For example, new independent claim 2 recites “analyzing the content relative to content in at least one of the plurality of semantic objects” and “creating an association between the created semantic object and any of the at least one of the plurality of semantic objects based on the analysis”. Neither Gupta nor Kroenke teaches analyzing content in a semantic object “relative to content in” another semantic object and creating an association between the semantic objects “based on the analysis”. As such, the subject matter of claims 2-28 is neither anticipated nor rendered unpatentable by Gupta or Kroenke.

Conclusion

Favorable consideration of new claims 2-28 is requested.

It is believed that all of the pending claims have been addressed. However, the absence of a reply to a specific rejection, issue or comment does not signify agreement with or concession of that rejection, issue or comment. In addition, because the arguments made above may not be exhaustive, there may be reasons for patentability of any or all pending claims (or other claims) that have not been expressed. Finally, nothing in this paper should be construed as an intent to concede any issue with regard to any claim, except as specifically stated in this paper, and the amendment of any claim does not necessarily signify concession of unpatentability of the claim prior to its amendment.


This amendment is being filed with an Request for Continued Examination (RCE), therefore, please apply the RCE filing fee of \$790 and extra claims fees of \$300 and any other charges or credits to deposit account 06-1050.

Date: _____

7/27/07

Fish & Richardson P.C.
60 South Sixth Street
Suite 3300
Minneapolis, MN 55402
Telephone: (612) 335-5070
Facsimile: (612) 288-9696

Respectfully submitted,



J. Richard Soderberg
Reg. No. 43,352

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant	: Nova Spivack	Art Unit	: 2162
Serial No.	: 10/720,031	Examiner	: Jean B. Fleurantin
Filed	: November 20, 2003	Conf. No.	: 2540
Title	: METHODS AND SYSTEMS FOR CREATING SEMANTIC OBJECT		

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

MARKED UP VERSION OF SPECIFICATION

METHODS AND SYSTEMS FOR ~~MANAGING OFFERS AND REQUESTS IN~~
~~A NETWORK-CREATING A SEMANTIC OBJECT~~

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims priority under 35 USC § 119 to
5 Provisional Patent 60/427,550 filed on November 20, 2002, titled Semantic
Network Platform, Framework and Application, incorporated herein for all
purposes.

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

10 The present invention relates generally to computer software and
network applications. More specifically, it relates to software for
implementing knowledge management systems and knowledge representation.

2. DISCUSSION OF RELATED ART

15 Knowledge workers, teams and organizations routinely work with a
large and complex array of information. This includes e-mail messages,
instant messages, chats, discussion postings, calendars, contact and to-do lists,
documents, photos, maps, and database records. This information also
includes tacit knowledge and expertise that resides only in people's heads.
20 The average knowledge worker interacts with several dozen information
types, hundreds of Web sites, and dozens of different applications. Existing
information systems are focused mainly on data, rather than on relationships

between data. There is a growing need to enable applications and users to see how various types of information are related across different information systems and locations. However, there is no tool for connecting, managing and sharing this information in a unified way.

- 5 The growth of the Internet, as well as the increasing amount of information it contains, are leading to serious problems for many computer users. In particular, they are leading to a problem referred to as “information overload” in which parties are overwhelmed by more information than they can effectively process, navigate, search, track, respond to, utilize, cope with,
- 10 or manage given limited time and resources.

- A related problem is “information complexity” in which, due to the sheer volume of information choices on the Internet, and its disassociated nature, is making it overly difficult to locate particular desired information when it is needed. Another related problem is “dis-integration” that arises due
- 15 to incompatible or nonstandard information and services, which leads to software and service incompatibilities, as well as obstacles to processing and managing information effectively. Another problem is “spam” that arises when Internet participants receive unsolicited, unwanted, or irrelevant information from other parties on the Internet. An additional problem that is
- 20 related to spam is “lack of targeting” which arises because information providers such as publishers, advertisers, and marketers are unable to effectively distribute their information to appropriate, interested parties, due to lack of information about the interests and policies of those parties.

Another related problem that is also related to spam is called “lack of personalization” which arises when parties on the Internet are unable to effectively subscribe to, filter or control the information they get from others. Another problem is “lack of privacy control” which results because Internet participants are unable to effectively control what information about themselves is shared with or by other parties on the Internet. Yet another drawback is “information deficit” that results when parties are unable to find, or do not receive, the information they need or are relevant to, even though it is available somewhere on the Internet or even on their own computers.

These problems, and related problems, are becoming serious obstacles to knowledge work, commerce, collaboration, publishing, marketing, advertising, search, communications and communities. In particular these problems are reducing the productivity of Internet participants. Parties must spend increasing amounts of time and resources searching for information they seek, trying to ensure that they receive information they want from others, trying to block or delete unwanted information received from others, responding to information they receive from others, managing and organizing information they want, tracking changes to information of interest to them, trying to distribute relevant information to others appropriately and trying not to mistakenly distribute unwanted or irrelevant information to others. With the expanding and pervasive use of the Internet and its increasingly central role in relationships, interactions and transactions of all kinds, those entities that provide content and/or Internet software tools and services are searching for and implementing ways to solve the above problems. However, attempts to

solve these problems face numerous obstacles. Presently the Internet is comprised of many separate infrastructures and software tools that are used for different modes of communication. For example, e-mail communication takes place via e-mail servers and client software applications that

5 communicate via specialized e-mail messaging protocols, yet Web searching for example takes place using search engines and databases that are accessed via Web browser software and Web transaction protocols. Thus, even if one were to solve the problem of information overload for e-mail it would not necessarily solve this same problem for Web searching.

10 A principal problem stems from present systems' inability to store, route and use meta-data about the data resources that they manipulate. It is therefore a goal of the present invention to provide a comprehensive solution to these limitations, in the areas of information overload, search, sharing, collaboration, communication, transactions, knowledge management,

15 information distribution, and automated and manual manipulation of computer-stored data and resources, allowing information to be connected in meaningful ways.

Using traditional search systems, parties seeking something enter queries that are tested against databases of information that are provided by

20 one or more parties with things to offer. If matches are found, the seekers are notified with links to the appropriate provider. One problem with such systems, however, is that they do not work in reverse; there is no way for providers to locate seekers who want what they offer. Instead, providers must wait passively to be found by seekers. Seekers on the other hand, must do all

the work. Another problem is that it offers only search by keyword; there are no mechanisms that support higher-level organization of the information.

Providers who want to be found may resort to marketing in order to reach seekers. For example, many search engines provide an option to buy keyword advertising, enabling providers to market what they offer to seekers who enter relevant queries. Although they do this, they do not enable providers to search for seekers who want what they offer, nor do they help them locate seekers who are not presently searching but are still interested. Thus providers must use external marketing channels such as direct email, banner advertising, paper-based direct mail and other forms of advertising to locate interested seekers. These inefficiencies result in increased transaction costs for seekers and for providers.

The present invention provides a single universal underlying infrastructure for managing information overload, distributing, locating and filtering information between information providers and recipients that works equally well across all types of Internet relationships, interactions and transactions. This single solution can be used to route and filter e-mail and instant messages, search the Internet, share files, publish and subscribe to information, market and advertise, coordinate and collaborate with others, personalize services, engage in online communities, and improve the efficiency of on-line commerce between buyers, sellers and intermediaries.

SUMMARY OF THE INVENTION

In one aspect of the invention, the knowledge network and semcards enables intelligent matching of offers and requests, involving all types of
5 information and knowledge, including information such as classified ads, data about products and services, or knowledge, expertise, ideas, suggestions, opinions, and other forms of tacit knowledge. The present invention is capable of intelligent matching of offers and requests, involving all types of knowledge: Information, ideas, suggestions, opinions, products, services, jobs,
10 events, people, skills, etc, using semcards and semcard-like structures, creating a bi-directional marketplace on the Internet, desktop or intranet. The invention enables parties to search and do marketing in the same way, in the same environment.

A semcard can be designated as an offer or a request and for various
15 purposes including advertising, offering items, or finding items. With direct targeting a semcard is sent to ~~specific~~specific recipients with which the semcard's creator has an existing relationship. With indirect targeting, on the other hand, a semcard is sent to recipients who satisfy various criteria. When the semcard has been specified to the user's satisfaction it can be test-posted.
20 Using semantic routing, semcards that represent offers, requests, and queries, can be routed semantically between nodes on the network. The routing profile describes salient features of the semcard, as deemed necessary for supporting

efficient routing of semcards. Collections of semcards can also be matched or compared in a knowledge network. Users can also create new semcard templates or extend the ontology, and share these extensions with other users in the network.

- 5 In another aspect of the invention, the semcard management application provides statistics on phenomena such as supply and demand trends for particular types of offers, requests and semcards, number of users with a particular interest profiles, number of potential matches for particular advertisements, and distribution of the user population along multiple
10 dimensions.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood by reference to the following description taken in conjunction with the accompanying drawings in which:

- 15 FIG. 1 is a block diagram of the basic semcard structure and an example of a semcard containing sample meta-data.

FIG. 2 is a block diagram showing relationships among a semcard, a sample referenced semcard, computer-readable data pointed to by the semcards, and an ontology.

- 20 FIG. 3 is block diagram showing another example of a primary semcard referencing a second semcard both of which reference the same ontology.

FIG. 4 is a block diagram showing the various lifecycle stages of a semcard.

FIG. 5 is a block diagram showing numerous semcards and links comprising a knowledge network.

5 FIG. 6 is a block diagram showing two semcards connected by a link semcard defining a relationship between the two semcards.

FIG. 7 is a flowchart illustrating a method of the internal process for creating a semcard.

FIG. 8. is a sample screenshot from the user interface of semcard management application showing various panels.
10

FIG. 9 is a schematic diagram illustrating an initial state of a simplified example of the notion of contexts in the semcard management application.

FIG. 10 is a schematic diagram illustrating a context being populated with relevant semcards.
15

FIG. 11 is a schematic diagram showing the appearance of pointers to semcards upon selection of a context.

FIG. 12 is a schematic diagram showing the creation of a sub-context to a super-context.

FIG. 13 is a schematic diagram showing the appearance of pointers to semcards upon selection of a sub-context.
20

FIG. 14 is a schematic diagram showing the appearance of all pointers to semcards originating from a super-context and its sub-context upon selection of the super-context.

FIG. 15 is a schematic diagram showing the association of a rule collection semcard with a particular context.

FIG. 16. is a block diagram showing a selected entry point, a results panel, and a viewer panel with tabs indicating various displays.

5 FIG. 17 is a block diagram showing contexts and a results panel containing various sorted semantic dimensions and values.

FIG. 18 is a block diagram showing a pool of semcards, their semantic dimensions and values, and their relationship to an ontology.

FIG. 19. is a block diagram showing a filter panel container with one
10 filter panel.

FIG. 20. is a block diagram showing a new filter panel appearing as a result of user selection of a filter panel feature.

FIG. 21. is a block diagram showing a third filter panel appearing as a result of user selection of a second filter panel feature.

15 FIG. 22 is a block diagram showing the results of a user selection of a third filter panel feature.

FIG. 23 is a sample screenshot from the user interface of the semcard management application showing a “stacked” layout of filter panels.

FIG. 24 is a block diagram showing the “stacked” layout of three
20 consecutive states of a filter container upon the application of filters on selected features.

FIG. 25 is a schematic diagram showing the How tab on the Relationship semcard, allowing permissions and default policies to be set.

FIG. 26 is a schematic diagram of a knowledge network consisting of numerous semcard management application peers with relationshipsrelationships.

FIG. 27 is a schematic diagram extending FIG. 26, showing more
5 complex relationships between peers.

FIG. 28 is a schematic diagram showing routing of semcards using servers in a peer-to-peer network.

FIG. 29 is a schematic diagram showing routing of semcards using servers in a network of peers and servers.

10 FIG. 30 is a schematic diagram of matching mechanisms used on semcards.

FIG. 31 is a schematic diagram showing details of matching two semcards.

DETAILED DESCRIPTION

15 Reference will now be made in detail to a preferred embodiment of the invention. An example of the preferred embodiment is illustrated in the accompanying drawings. While the invention will be described in conjunction with a preferred embodiment, it will be understood that it is not intended to limit the invention to one preferred embodiment. To the contrary,
20 it is intended to cover alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

The present invention presents a comprehensive system for augmenting computer-mediated collaboration and communication of knowledge and information, using the concept of semcards, that can be interconnected via a particular type of semcard that functions as a semantic link, to form distributed knowledge networks.

A semcard is a semantic software object that contains slots with semantic tags, and content, all of which can be represented semantically, optionally using an ontology, and rules embodying optional rules regarding automation, goals, display, access permissions and other policies, sharing, and other operations of the semcard and its target referent. The target referent is what the semcard is about: it is an entity or concept that the semcard represents or describes and holds metadata about. It can be a physical entity such as a living person, a software entity such as a data record or word processing document, or an intangible entity such as an idea or thought or feeling. Any type of digital object or information can be attached to a semcard, e.g. a digital certificate, a link to a web page or a product or service offer, an SKU, a data record in a database, or knowledge item, software, or a file or media object, media streams, a link to a remote Web service, etc. Semcards can also be used themselves to represent the relationship between other semcards, for example, that the person is the author of the idea.

A semcard can be thought of as a form with fields or slots, and has two incarnations, template and instance, which correspond roughly to the object-oriented programming concepts of object template and object instance.

As shown in further detail in FIGS. 1 and 2, each semcard has numerous semantic dimensions, also referred to as meta-tags in the semcard template. For example, for a semcard representing a material object, a semantic dimension (meta-tag) can be “color”, which contains a particular value (meta-data), and restrictions on what kind that value may be. (Semcards are also used to represent the semcard templates themselves.) To fill out a semcard, an instance is made of a semcard’s template, and selected slots of the instance are filled with values. Each semcard instance, its semantic dimensions, and their values for each semcard, can be stored on a computer readable medium as an XML (eXtensible Markup Language) object, using the RDF (Resource Description Framework) format, any binary storage format, or other chosen format. Semcard templates can be created by designers, who hand-pick the meta-tags that define the semcard’s referent target. Semcards can also be created dynamically and automatically through automated selection and organization of meta-tags from a pool of metatags; the selection of meta-tags and their organization in the semcard being driven by heuristic rules, e.g. by the meta-tags’ popularity with a group of semcard users and authors.

Referring to FIG. 1, a semcard 1-1 contains rows, called slots, 1-2 for storing metatag-metadata pairs, tags on the left side 1-3, metadata on the right-hand side 1-4. A semcard 1-2 with example tags 1-6, 1-8, 1-10, 1-12, 1-14, 1-16 and example values for each tag 1-7, 1-9, 1-11, 1-13, 1-15. Slot 1-17 would hold a reference to a link semcard, as explained further below and in FIG. 6. In a preferred embodiment of the present invention, semcards are defined in

XML that can be easily transformed to/from other data formats, including other XML formats, HTML, RSS, RDF, SHOE, DAML+OIL and OWL, as well as other application specific data formats. For the purposes of the present invention, the size and complexity of a semcard can vary. A collection of
5 semcards linked together is referred to as a knowledge network. In a preferred embodiment, people can access and manipulate individual semcards, and knowledge networks, via desktop tools, as well as with standard Web browsers.

Referring to FIG. 2, a semcard 2-1 contains data 2-2 which references
10 2-3 to an external entity 2-4, stored on a computer-readable medium 2-5 (The link 2-3 to the external entity 2-4 is itself a semcard, as shown in FIG. 6.) The semcard's 2-1 tags 2-6 are defined 2-11 in an external ontology 2-7, which has standard nodes 2-8 and relationships between them 2-9. The semcard 2-1 contains data 2-12 which references a display specification 2-14, said display
15 specification containing data 2-15 referencing 2-16 an application 2-17, stored in a computer-readable medium 2-18, said application being used to view and manipulate the entity 2-4 referenced by the semcard 2-1. The display specification 2-14 containing tags 2-19 which are also defined 2-20 in ontology 2-7. This ontology can be the same or a different ontology that
20 defines the tags for the semcard 2-1. (The link 2-16 to the external display instructions 2-17 is itself a semcard, as illustrated in FIG. 6.)

Data in semcards can be defined using an ontology. An example is a data element like 'Dalmatian' as the data value for the tag 'breed'. Referring to FIG. 3, a semcard 3-1 contains a reference 3-13 to a display specification 3-

14, and data elements which reference 3-8 nodes in an ontology 3-7, stored in a computer-readable medium 3-5, said ontology 3-7 containing nodes and links. Said display specification 3-14 containing data which also reference 3-9 nodes in an ontology 3-4. This way both the tags of a semcard and its data can
15 be defined in an ontology, the benefits of which are an ability to compare two or more semcards created by separate users at different times.

Although the amount of metadata in a single semcard can be very small or extremely large, a semcard is intended to be of a convenient size from a cognitive standpoint, so as not to overload its user with too much
10 information. For example, a semcard describing an automobile would have the typical "common sense" data about its color, type, seating, engine power, etc.; if more information was desired to be represented about the car's engine, a separate semcard could be created for this purpose, and linked to from the automobile semcard. This way the relationship between single semcards and
15 collections of semcards – or knowledge networks – is kept at a cognitively manageable ~~manageable~~ ratio.

In a preferred embodiment, part of the metadata of a semcard represents its lifecycle stages. There are four lifecycle stages of a semcard: (a) Draft, (b) active, (c) inactive, (d) deleted. FIG. 4 is a block diagram showing
20 the lifecycle stages 4-1, 4-2, 4-3, 4-4 of a semcard. A semcard starts out in draft stage 4-1, and transitions from this sequentially through stages 4-5, 4-7, 4-9 based on events 4-6, 4-8, 4-10 which are initiated by the user or automatically initiated through rules codified in the semcard's policies or automation instructions or elsewhere, or by other means. The transition from

draft 4-1 to active 4-2 happens through an activation event 4-6, which is initiated by the user, by automatic rules, or by other means. The transition from active 4-2 to inactive 4-3 happens through de-activation event 4-8, which is initiated by the semcard's maximum lifetime, by user-driven events, by
5 automatic rules, or by other means. The transition from inactive 4-3 to deleted 4-4 happen through a deletion event 4-10, which is initiated by a user, by the Semcard Manager's determination that the semcard is no longer needed, by other automatic rules, or by other means.

Referring to FIG. 5, a semcard 5-1 unifies information about a person,
10 using pre-defined slots with pointers 5-14 to relevant information, including their names 5-3, date of birth 5-5, contact information 5-7, addresses 5-9, friends 5-11, and authored document 5-13. Semcards 5-2, 5-4, 5-6, 5-8, 5-10, 5-12 relate each relevant semcard to the person semcard 5-1. In a preferred embodiment, slots on semcards can be defined to be required slots, i.e. belong
15 to the object, and thus traveling with it when shared, published, copied, etc. In this example, the slots for a person's name and address are defined as required slots, and thus by default belong to the person semcard 5-1, whereas the 'Friend-Of' link is optional. When a semcard is shared, its optional slots require the owner of the object to explicitly designate them as shared; the
20 required slots are shared by default when their parent object is shared. In the example of FIG. 5, if semcard 5-1 were to be shared, the semcards 5-10 and 5-11 would not be shared, by default – they would have to be specifically designated as shared.

Semcards are intended to represent a variety of common types of things, and templates for a variety of common things are provided by the semcard management application, including relationships, interactions and transactions including communications such as e-mail, instant messages,

5 alerts, bids, announcements, questions, answers, invoices, receipts, proposals, search queries, invitations for participation in relationships and events and activities of various types, content, files, advertisements, brochures, catalogs, publications, subscriptions, opportunities, coupons, etc. In addition to these specific types of data and knowledge, semcards can also represent ideas,

10 concepts, and other forms of tacit or intangible knowledge.

The following is a partial list of what semcards can be used to exchange and share: e-mail messages, instant messages, discussion threads and postings, chat messages, XML messages, directory listings, files, advertising and marketing, invitations, tasks, orders, invoices, receipts,

15 information about auctions and bids, charges and payments, software and software updates, multimedia content, referrals for things, polls, surveys, reviews and opinions, data records, data streams, questions and answers, Web sites and Web pages, alerts and notifications, pop-up alerts, on-screen and audio notifications, information about events, information about opportunities,

20 information about products and services, information about people, organizations and groups, information about topics, classified ads, publications and subscriptions, commands and reports, information about relationships, ontologies and ontology branches. Semcards can also be used to buy and sell things and other transactional tasks, to trade things, track interests

and watch for events, filter information, publish information, subscribe to information, distribute information or digital products and services to targeted recipients, distribute information to fuzzy sets of recipients, interact anonymously, sell pay-per-view links to information, buy and sell semcards,

5 transfer funds between parties based on transactions following from matchings between their semcards, brokering relationships and interactions between parties, send or receive semcards to/from parties who are indirectly related to a party by varying degrees of social distance (sequences of indirect relationships of varying number that connect the parties).

10 Semcards can be generated either manually by a user or automatically by the system. For example, user A finds a useful URL and creates a semcard for it. He includes his comments and description of the web page. The semcard gets metadata from the URL's web site automatically. User A links the semcard to projects and documents for the team. user A stores the

15 semcard in his semcard space. By doing so user A can be notified of changes to the site. He gives a copy of the semcard to user B who saves it all in his semcard space and adds his own data and comments, and attaches a file to it. The semcard that user A has is automatically updated to reflect user B's changes. It is synchronized with user B's copy and now gives user A access

20 to user B's comments and the file that user B attached, which can stay on user B's semcard space on his peer or can be stored at another location.

Semcards can also be created fully automatically, for example, by data mining various resources on the Internet after those resources have been

created. This can happen in advance of the semcards being needed or on-demand such as in response to queries.

Semcards can be created simultaneously with the creation of the content they will represent by including a semcard creation procedure within applications such that upon certain events they trigger semcard creation. Alternatively, semcards can be created via a semcard creation daemon that watches file directories and applications for various events and then triggers semcard creation. Alternatively it can be done manually by the user from a menu embedded in applications. In all these scenarios various events may be set to trigger semcard creation and modifications:

- saving a document or data item
- creating a document or data item
- opening/viewing a document or data item
- modifying a document or data item
- transmitting a document or data item
- receiving a document or data item
- deleting a document or data item
- integrating documents or data items with existing file servers,

databases or search engines

Semcards embody metadata about their target reference as well as their own structure; they are self-describing and are structured in a type-attribute-value form, where type is the unique type of the data they represent, attribute is one or more metatags, and value is one or more metadata elements. Semcards can represent anything, and they provide detailed information about their own structure, meaning, functionality, content, relations, policies, permissions, procedures, history, statistics, authors, users, owners, goals, and state. Semcards are both machine-readable and human-readable; human-

readable because they contain rules and policies relating to how they interact with and are manipulated and read by humans. A semcard's associated display rules dictate how the semcard itself— as opposed to its target reference — should be displayed to the user. These rules can specify, for example, how the

5 semcard should be displayed depending on the display device used, which render is being used, and what purpose the semcard is being viewed for. The rules can specify how, for example, meta-data (or data values) in the semcard should be organized and what labels should be used for them, if any, as well as what aspects of the semcard appear as interactive elements in the interface,

10 and the results of specific interaction with those elements.

Semcards can be transmitted over computer networks using email, traditional network routing and communications protocols, Web protocols, peer-to-peer and Web services protocols, new semantic routing protocols, etc., and can be stored on any computer-readable media. Semcards can act as

15 search queries, by linking them to semcards designated as offers or requests, and specifying acceptable ranges and matching rules for the various semantic dimensions and values of the semcard, as described below.

The benefits of semcards are evident directly to their human users in their daily work with information, augmenting current computer systems in

20 many ways, including but not limited to more efficient ways for users to navigate, browse, search, share, manipulate, display, link, organize, access, and store their data. Semcards are also beneficial to current computer systems by enabling more intelligent and accurate automatic manipulation of information, including but not limited to: routing, storing, matching,

searching, meta-tagging, integrating, organizing, filtering, form-filling, linking, and displaying of information. Rules give the owner of a semcard direct control over how semcards, and their referenced resources, are searched, matched, shared, duplicated, copied, on the owners' own computers

5 as well as over a network of computers such as the Internet. These rules can be event-driven or periodic. A rule could for example specify that "when recipient gets this message, send me a receipt and also forward receipt to a database; wait for a reply from recipient; if no reply is received, remind recipient to send a reply in 3 days." Semcards can represent streaming media,

10 specifying the metadata about the source from where to get the data, and what to do with it. This can be set up to be either pull or push, with policies defining conditional behavior for the standard event types associated with such streams (i.e. glitches, delays, overflow, loss of connection, end of stream, etc.).

15 Semcards and their copies on other systems can be set to have a time to live (TTL), such that they expire after a set period of time. Their rules will then determine whether they should be deleted, compressed, etc., and whether the original should be notified. Semcards can also be manually expired, independently of their TTL, by their author. For a local semcard this is simply

20 moving the state of the semcard from active to inactive. For a remote semcard living elsewhere on the network this involves sending a ~~special~~special termination signal with the particular semcard's unique ID. The same ~~meehanisms~~mechanism can be used to rescind a semcard that has already ~~been posted~~been posted.

- Semcards link to other semcards using a Link semcard. Link semcards are a kind of semcard that contain rich metadata about the relationship between things, as represented by two connected semcards. In FIG. 6 semcard 6-1 points to semcard 6-3 via semcard 6-2. In a preferred embodiment, each semcard has its own existence, history, and global unique identifier (GUID). For example, a Document semcard can be linked to a Person semcard using an Author-Of Link semcard. A constraint system can be provided such that only certain kinds of links can represent relationships between certain kinds of semcards. The constraining system represents the logical way in which semcards can be linked. More specifically, it represents ontological knowledge about how the world is composed; a link between two semcards should 'make sense' or be comprehensible to the semcard management application and its user, that is, the link should be consistent with the ontologies contained in the system.
- 15 Semcards can be used to integrate semantic representation with legacy data. For example, the system can supply a simple server that can receive a query from a network and then translate it into one of several popular legacy formats (such as SQL) or custom formats (defined by admins) and transmit it to various legacy systems, then get results and reformat them as semcards,
- 20 then supply these back to the party issuing the query. A query can be received at a network node for any white papers about software applications. The node can then translate this query into a query to a local legacy search engine. The search engine can conduct a legacy search of local databases and return any search results to the node. The node can then either embed and return those

results within appropriate semcards on the fly (if the results are rich enough) or further analyze any found documents in order to create semcards for them to then supply to the party issuing the query.

Another approach is to datamine entire collections of digital entities
5 and create semcards for the selected digital entities in advance so that semcards do not have to be created in real time. Searches are executed against the collection via standard legacy search engines and when results are found instead of reporting the raw results or attempting to generate semcards at that time, the corresponding pre-existing semcards for those digital entities are
10 returned to the user from a database of semcards.

Data mining can proceed in at least two ways: unstructured and structured data mining. Unstructured data mining involves various artificially intelligent agents or other software ~~artifical~~artificial intelligence applications that scour resources and determine the identity and nature of these agents.
15 Based on this they can then create semcards for representing the resources. Structured data mining allows a schema to be created that guides the agents directly in creating particular classes of semcards. For example, an agent can be created to make “white paper” semcards with particular policies, targeting and attributes for qualifying documents in some pre-defined, well-structured
20 content collection. The agent scours the collection and for each qualifying document it then creates a semcard from the semcard template, automatically filling it in with information about the white papers using the agent’s built-in intelligence. Thus, the agent already knows that the documents in the collection are white papers having certain attributes and policies so it can

more easily create semcards for them less need for advanced artificial intelligence.

The semcard management system ensures that semcards and any content they refer to are not separated, i.e. that the targets of semcards are not lost. A mechanism may be provided such that pointers from semcards to target content are maintained so as to have correct addresses for the target content. One solution is to have a semcard representing a target content, such as a document, connect to the target via a link semcard. In addition, when either semcards or the target content objects are moved, the pointers are updated or the associated objects are moved together. Another solution is to wrap content objects in semcard containers such that the content objects do not exist outside of such wrappers. That is, documents are stored inside of semcard objects. Another approach is to move any objects described by Semcards into a protected storage environment such that they can only be moved under the supervision and policies of the Semcard management application.

Another approach is to embed semcards into documents, websites, products, etc. This can be done, for example, by embedding semcard tags in content or by attaching semcard files to content ~~objects, by objects, by~~ either including the files as hidden data in the documents, or as links or attachments to the documents.

Another approach is to maintain an association table of mappings between semcard files and target content files such that when files are moved or changed the corresponding entries in the association table is updated. This

table enables the associated semcard(s) to be found from any file, and the associated file(s) to be found from any semcard. The association table must be periodically updated on a regular basis or at least updated when changes are detected/made to semcards or any files that are indexed in the table.

- 5 To accomplish this a daemon could be provided to watch for changes and update the association table accordingly. There are various ways to implement this. In one case daemons can report to some central location what files they have so that other daemons can locate those files. When files are moved to locations that are not watched by daemons objects are wrapped in semcards or semcards are embedded in objects when possible.
- 10

- A semcard can be divided into four main sections, (a) the *What* – the attributes of the offer/request and any further content payload, (b) the *Who* – the identity of the sender and the specification for what recipients are to be targeted, (c) the *How* – any goals, rules, policies, reply methods, etc., and (c)
- 15 Where – the history of this semcard, modifications, copies made, who has viewed it, links to prior versions of it, etc. These are conceptual categories of organization that may exist in isolation or exist with other features for organizing the semcards' parts; this division can, but does not need to, correspond to the way the semcard is represented to the use.

- 20 1) The *What* part of a semcard describes whatever the semcard represents and/or carries, for example: a Web site or document, an opportunity, and advertisement, data or knowledge, a file, an event, an audio recording or electronic book, a Web service, software object, a collection of

other semcards or a non-digital product or service, or ideas and tacit knowledge.

2) The *How* part of a semcard defines the semcard's policies and procedures.

5

3) The *Who* part of a semcard contains an authenticated person (visible or anonymous) representing the owner of the semcard. This part also contains addresses for various recipient individuals, groups, or a fuzzy definition of the qualifications for valid recipient individuals and groups, lists of users who have modified, copied, received, or deleted the semcard, as specified by the semcard's policies about what kind of such data should be stored, and other information regarding users or agents.

10

4) The *When* part of a semcard contains a compact representation of the history of events related to the semcard. The decision about which events are stored with the semcards, which events are linked from to the semcard, and which events are ignored, are determined by the rules related to the semcard's history.

15

A method of creating a semcard is described in FIG. 7. At step 702 a user selects an empty instance of a semcard type, and fills it in with content values. The semcard instance is given a global unique identifier (GUID). When creating a semcard manually or a document, for example, the author will be provided with a selection of valid values for a particular slot, as defined in the ontology, such as "author of", which will display instances valid for the slot, such as names of particular people or organizations (only people and organizations can be considered "valid authors" of documents).

20

25

This would typically include all names of organizations and individuals (all potential authors) in the user's semcard space.

In the semcard system of the present invention, all data items are stored on disk continuously, that is, immediately after they are entered by the user, so the user never has to manually "save" a semcard – this is done automatically. Once the semcard is created, the user can commit – or post – the semcard instance. Referring to FIG. 7, at step 704, the user creates rules for the semcard management system, as well as rules pertaining to types of semcards, and instances of semcards. The rules can specify, among other things:

- 1) Whether the semcard can be linked to by others
 - 2) Whether various operations on, or modifications of, the semcard need manual approval of the owner; and
 - 3) How the semcard's content should be updated automatically
- At step 706 the system receives a new rule, either created by the user or automatically by the system, or by some external process or third-party, and compares them with existing rules it already stores. These rules can apply to semcards, to the semcard management application itself, or collections of semcards, in which case they are referred to as "global rules". These rules may be related to access privileges, how information is displayed in the user interface, or any other feature of the system that can be controlled by rules. User-created rules, as well as default rules provided with the semcard management application, are managed by an automation component with a rule engine.

At step 708 the automation component checks for conflicts with existing rules in the user's semcard system space. If no conflicts are detected, and the creator of the rule has permission to submit the rule, the rule is stored and becomes part of the system's rule set at step 710.

- 5 Some rules may be stored with the semcard and processed by other components, for example, access privileges maybe handled at a lower level. Access privilege rules differ from display rules in that they are each represented differently.

- Semcards can be transformed to various formats using methods in the
10 semcard system. One format is intended for efficient storage in memory. Another format enables efficient transmission of the software objects over a network. Another format enables interchange with third parties. For example, this format may be serialized XML or RDF or other applicable format. Semcards, and any part of their metadata, can be easily encrypted.

- 15 Semcards, and any part of their metadata, can be digitally signed to authenticate their origins and trustworthiness, and to control access to them, and manipulations of them.

- Many users may create links to a particular semcard external to the user's semcard space on a network; each user may create a different set of
20 links. The result is a network extending beyond the user's peer but residing on each user's semcard management application which relates to that particular semcard. If these users share their network with the world, it is now possible to traverse a knowledge network that is the sum of all the users' networks, where the center point is the particular semcard.

When a semcard has been posted, no matter who it is addressed to or how, it will be handled according to its own rules, and other rules in the system. The content of the semcard can be mined and related, and automatically linked, to other semcards in the system (via newly created link
5 semcards). Mining is typically controlled by global rules for the semcard system. The process finds connections between semcards by examining values and semantic dimensions in each semcard. One of these tasks is checking for duplicate or repetitive data and concepts to reduce data storage. It can also link the new semcard with existing semcards using inferences and other
10 techniques.

The system also accepts plug-ins that perform as experts in determining where and when there may be connections between semcards. For example, a plug-in may be an expert in corporate formations and organizations. Thus, it knows that an organization has a founder. If a
15 semcard is created for an individual and that individual's name is also in an Organization semcard, the plug-in can draw the inference that the two semcards should be linked based on the plug-in's own rule set, which enables it to draw the inference. The system can also make any obvious corrections to values in the slots.

20 On a network, as copies of a semcard move around, a target referent is handled according to the semcard's policies. The options available are 1) keeping the semcard and the payload together at all times; 2) keeping them separate at all times; and 3) keeping the payload within close proximity so it may be cached. For this purpose, the target reference object can be contained

within the semcard, can be kept with the semcard at all times but separately, or it can be kept remotely.

- As described above, a link between two semcards is itself a semcard. However, the process for creating a semantic link is somewhat different from the method of creating an object semcard. Although the user may often manually create a link, its content values are typically managed by the semcard system rather than explicitly by the user (although the user can, under special circumstances, modify a link's content). Often the links are created fully automatically. Links created by the system may be assigned a confidence value, which represents the automated ~~system's~~system's estimation of its correctness (i.e. is this the right type of link ~~between~~between these two other semcards). Generally, a human-created link will not have a confidence value, or have the highest confidence value possible (except in cases where the human user isn't certain that what they are representing is correct). All links—like all semcards—have an author, whether an automated process or a human. This allows a user to perform searches and queries of the system specifying that links should be authored by a human, or by the system, with a certain confidence value.

- To avoid having an object semcard lose a referent target, whether a document or other thing, the relationship between the two is implemented using a Link semcard. A link semcard always connects two other semcards, the source and the target, making links directional. The semantically inverse meaning of any link can be defined in its ontology; e.g. the inverse of “author of” is “authored by”. These links are themselves full semcards; there are

typically no direct – or “flat” – links from a semcard representing a target referent document and the referent target document or item itself. This means that the link has rich information about the relationship between the semcard representing the referent target object and the referent target object itself, allowing the link to be manipulated in the same way as other semcards, via filtering of its values and semantic dimensions.

In certain exceptional cases, link semcards can be “folded into” the source semcard that it links to, to be treated as a “flat” link with no extra meta-data about the link itself. Optionally the whole Link semcard can be folded into the semcard source. This is sometimes done for efficiency or convenience when moving semcards around in a computing device or on a ~~network~~ network.

As mentioned, a semcard has a particular type which is typically defined in the system ontology. A user can expand and edit the types of semcards, either by adding to the ontology, modifying the ontology, or adding undefined metadata directly to the semcard. Such additions and modifications can be shared with other peers using the semcard system.

The peer desktop application described here is a system for managing semcards and semantic information; it is a general semantic browser, as well as a dedicated application for managing semcards. The application has several functional components which include 1) an identity manager, 2) a user interface management component; 3) a database component; 4) a network component; 5) an automation component; and 6) a relationship management

component. Providing more detail, each semcard peer node may consist of the following components:

- 5 • Fuzzy matching engine for estimating conceptual distance between semcards.
- One or more schedulers for scheduling node events.
- Monitoring module that computes statistics based on server events.
- Backup manager that manages backup schemes.
- 10 • Manager for plug-ins that do e.g. mining, logging, monitoring, schedule-based or event-driven behaviors, display rendering, automatic linking, filtering, etc.
- Test post facility, for testing semcards and queries before they are posted.
- Security, encryption and authentication manager.
- 15 • System administration suite.
- Router module that uses routing tables to forward semcards, queries, offers, requests, etc. to and from other nodes, depending on their meaning and priority.
- Display units for displaying system statistics in various ways.

20 The identity manager manages the identity of the semcard management application's users and groups, their communications, and the identity of match results for users and groups of users.

 Another component addresses relationship management. This
25 component manages personal information, essentially a user's identity or persona. It provides a secure way of managing the user's identity. It also contains data relating to all of a user's relationships and data necessary to communicate securely with other peers.

 The automation component operates as a single agent but broader than
30 a conventional agent, which has a particular expertise. The automation component has vast reach in the application in that it can communicate with and utilize all other components in the system. It can specify rules, e.g., rules

ensuring that a user is valid, that new rules are valid and that there are no detrimental effects caused by the addition or deletion of rules. Rules include permissions, automations, policies, and procedures, both those associated with semcards and those defined for collections of semcards, and for the

5 application in general. The automation component manages and executes automation in the background. The automation component provides the option for a single location where all rules are stored and managed. The automation component is able to process exceptions and can intelligently respond to user through the user interface; it has a knowledge base of user-

10 interaction methods, including graphical, textual, phone (using speech synthesis), and SMS (short message service). This enables the automation component to determine, using its interaction rules, how to interact with its user under various circumstances. For example, if a user is not at a home base, the automation component knows to send the user an SMS message.

15 The network component is an intelligent component that manages all data received by and transmitted by the application. This component manages and enables all peers, web pages, other networks, web services, other data sources to communicate with the system. The network component also knows when to alert other components based on the class of request or category of

20 data entering the system.

The user interface component provides a user interface for the semcard management application and has several sub-components. Referring to FIG. 8, they include a hierarchical list of "entry points" 802 ("MyThings" in the left-hand column), a filter panel container 804, a results panel 806, and a

viewer 808. The “entry points” column displays standard entry points into the semcard collection, such as type of semcard, as well as user-defined entry points; often these are the entry points that are used most frequently. The entry points can also represent RSS (Rich Site Summary) feeds, hard-disk folder hierarchy, and other traditional elements on a computer system. Entry points can be time-dependent, for example, an entry point could be called “Recently accessed,” which the system automatically ensures contains, at any point in time, only semcards that satisfy a particular set of criteria regarding time, e.g. that they have recently been created, viewed, or updated, or all three.

There are also “context” entry points. Contexts are a way to organize semcards into hierarchically arranged categories. In a standard hierarchical setup of contexts and sub-contexts, a sub-context’s input is its super-context’s output; hierarchical contexts thus being a semantic filter pipeline. Contexts can be applied to any entity which follows the object-with-properties model, as known in the art. Referring to FIG. 9, which presents a simplified example of contexts, a collection 9-8 of seven semcards 9-1, 9-2, 9-3, 9-4, 9-5, 9-6, 9-7, of two types, rectangles 9-1, 9-3, 9-4, and triangles 9-2, 9-5, 9-6, 9-7, with various semantic attributes, as designated by squares and circles inside the semcards, each attribute containing a value, as designated by the three letters a, b and c. A semantic context panel 9-9 contains three semantic contexts 9-10, 9-11, 9-12, that the user has created.

Referring to FIG. 10, to fill the contexts with relevant semcards, the user associates 10-13 desired semcards 10-1, 10-4, 10-5, with context 10-10, either by dragging them into the user interface or indicating their association

using other methods.

Referring to Figure 11, when the user now selects the context 11-10 (indicated by black), on the right-hand side of panel 11-9 pointers 11-14, 11-15, 11-16 appear pointing 11-17, 11-18, 11-19 to those semcards 11-4, 11-1,
5 11-5 which the user had dragged into the context. The pointers are created by using the GUID of the semcards; the semcards themselves reside in a repository. To the user, the title of the semcard may be used as the name of the pointers, for easy association. When the context 11-10 is selected, the context does a query to find all the semcards which belong to it, by doing a query
10 against a semcard storage.

Referring to FIG. 12, a sub-context 12-20 to context 12-10 can be created. The user now associates 12-26 other semcards into this context, but one of the semcards, 12-4, is the same as was associated with this context's 12-20 super-context 12-10.

Referring to FIG. 13, when the user selects context 13-20 (indicated by black), three pointers 13-21, 13-15, 13-22 appear which point 13-23, 13-24, 13-25, to the semcards 13-2, 13-4, 13-7 which were associated with this context 13-20 by the user.

Referring to Figure 14, the user now selects context 14-10 again
20 (indicated by black). Now pointers 14-14, 14-21, 14-15, 14-16, 14-22 appear that point 14-27 to the semcards 14-1, 14-2, 14-4, 14-5, 14-7 which are included both in context 14-10 and context 14-20.

Referring to FIG. 15, the user can now associate automation rules with the contexts. Here the user associates 15-23 a rule collection semcard 15-24

with context 15-10. The rule semcard may contain any number of rules 15-25 pertaining to this context, involving such things as automatically associating semcards with certain features with the context, deleting semcards, doing certain operations on the semcard collection in the context given certain events, and automatically making links between the semcards, inside the context or outside, according to certain principles, etc. Automation rules apply either to only the context that they are attached to, or to that context plus all its sub-contexts. Typically, rules apply only to the context they are attached to. Rules relating to all contexts can be added in the semcard management application as global rules.

Rules associated with a context can specify particular kinds of links that should be created automatically between particular kinds of semcards, given particular events. The rules can apply to only what's inside the context or to how what's inside the context should be manipulated relative to semcards outside the context. For example, rules for creating links between semcards in a context can be different from the rules about creating links between semcards inside a context and outside it.

Referring to FIG. 16, a selected context or entry point 16-20, filtering a subset of the semcard pool to be shown in the results panel 16-39, allows the user to select one of the semcard references 16-22 to be displayed in detail in viewer 16-44. Rows 16-41 of meta-tags 16-42 and meta-values 16-43 are displayed, along with the semcard's header 16-40. Tabs 16-45, 16-46, 16-47, 16-48 allow user to select various ways to display the semcard in viewer panel 16-44. The viewer panel allows users to view semcards in various forms.

These forms, shown as tabs, include a “Summary” view, a “Related” view, a “Preview” view, “Visualize,” and “RDF” (Rich Data Format). The viewer panel 16-44 shows a rendering of this semcard 16-22 according to its display policies for a form layout.

- 5 Referring to FIG. 17 a column header 17-26 is used to organize the names of various selected semantic dimensions 17-27, 17-28, 17-29, 17-30 so that the values of these dimensions 17-31, 17-32, 17-33, 17-34 for each semcard 17-21, 17-15, 17-22 listed in the results panel 17-39 can be used to sort them according to those values; the user can select a single dimension to
- 10 sort by. For example, if the values are strings, the semcards 17-21, 17-15, 17-22 can be sorted based on their unique values for that dimension.

- A second way to sort using the column header is to sort by one dimension first, then by another, then by a third, for as many dimensions as the user wishes. This would allow the list to be sorted, for example, by time
- 15 first, then alphabetically according to name, etc. One way that the user can do this is by specifying the order of each dimension in the column header, for example, to sort first by dimension 17-32, dimension 17-32 would be placed where dimension 17-31 is. This way, re-arranging the order of dimensions in the column header determines the order by which the semcards listed in the
- 20 results panel are sorted.

 The contexts can be used to support manually-initiated creation of multiple links, as when the user applies a command to create links of a particular type between two types of semcards for all semcard instances of those type in a given context.

The contexts can be used to support collaboration between the system's automated link generation mechanisms and the user. After a set of semcards have been added to a context, and links between them, the system can use these existing examples to present a more wisely chosen set of Links
5 when the user wants to create more links between the semcards within the context. The system can also create links automatically with higher confidence values, based on the positive examples of links created manually by the user.

A user can share one or more of her contexts with any other user with
10 which she has relationships, via the sharing mechanisms described herein. A user can also offer contexts using one or more Offer semcards.

Contexts can be used as a way to indicate which project a user is working on to other users on a network: When a user selects a context, this context is flagged as the context that the user is currently working in. For
15 example, if the user selects a shared context called "project x", this selection can be reflected in his co-workers' semcard management applications or other application designed to reflect the status of co-workers. The behavior of this feature is controlled via the context's rules.

A user can also select a current working context and perform
20 operations on the peer containing the context. These operations may not be directly on the context or the semcards within the current working context. For example, the user may perform Web searches, creates documents and folders, create graphics, and so on. All these operations, plus operations

directly on the current context and the semcards, are automatically associated with the current working context and the relevant semcards.

- The contexts can be used to do what is called “programming by example” in the art. To do this, a user creates a context and fills it with
- 5 “example” semcards. Then she instructs the system to extrapolate, or generalize, rules based on the sample semcards. This can be as simple as one step (e.g. a button click) or, alternatively, the user can give constraints about the rule creation such as “only apply this to new semcards received from relationships A, B and C”. The system will then use inferencing and rule
- 15 creation mechanisms to extrapolate rules from a created context. The user has several options for doing this. One is to create a context and fill it with semcards manually over a period of time (days, weeks), such that when the extrapolation command is given, the system has a rich history of the user’s manipulation and use of the context on which to base its generalizations.
- 15 Optionally, any subsequent manual additions or deletions from and to the context can be a trigger for the system to revise its extrapolated rule set for the context.

- The semcard management application has a filtering mechanism which allows a user to quickly select a subset of the full set of semcard instances
- 20 available. Filtering is done for the purposes of finding a particular semcard instance, for example, or zero in on a particular desired subset of semcard instances. The filtering is based on a collection of filter panels and free-standing rules. The rules determine which features, of the total feature set represented by the semcards in the semcard pool, are presented in the

interface, allowing the user to select from the multitude of semantic dimensions represented in the semcard pool, and the values that these dimensions hold. The filter consists of pre-conditions, which must be matched for the filter to fire (become active), a human-readable label, the property being filtered, and optional value(s) being filtered.

Referring to FIG. 18, a set – or pool – of semcard instances 18-8 contains two types of semcards, triangles 18-2, 18-5, 18-6, 18-7 and rectangles 18-1, 18-3, 18-4. These have semantic dimensions, represented here with white squares 18-10, black squares 18-11, white circles 18-8, and black circles 18-9. Each dimension contains a value, represented with the letters a, b, and c. The semcard types triangle 18-15 and rectangle 18-16 are defined in the ontology 18-13, as are their semantic dimension 18-17, 18-18, 18-19, 18-20 and the types of values 18-21 that these dimensions can accept. (Notice that an implementation of the invention would likely use strings instead of the graphical icons used here, for illustrative purposes, to represent these concepts, or a combination of both. Independently of the way a concept from the ontology is represented to the user, each concept in the ontology will simply be identified with a unique ID.)

Referring to FIG. 19, a filter container 19-23, shown as box X, holds a filter panel 19-24, a user interface concept, which displays two symbols 19-25, 19-26. These symbols represent the types of semcards in the semcard pool 9-8 shown in FIG. 9. The user can choose either of these symbols (e.g. by clicking) to designate a subset of the semcard pool, in other words, to apply that filter to the semcard instances in the pool 9-8. In the context of filter

panels, the semcard types, their various dimensions, and the values, are referred to as “features”. Rules determine which features are available for the initial filter panel, as well as each subsequent filter panel that appears as the user selects features in each one.

- 5 Referring to FIG. 20, showing a second state of the filter container labeled Y, after the user has chosen feature 20-25 in first filter panel 20-24, such that some of the semcard instances in the pool 9-8 have been filtered out (namely all semcards which are not of type triangle), resulting in a subset 20-28 with only triangles 20-29, 20-30, 20-31, 20-32. Further, a second filter
- 10 panel has appeared 20-26, containing a set of features 20-27 for further narrowing down the subset of semcards from the semcard pool 9-8.

- Referring to FIG. 21, showing a third state of the filter container labeled Z, the user has further selected a white circle feature 21-33, resulting in a new filter panel 21-34, with a set of features 21-35 that can be used
- 15 further reduce the pool of semcards. The selection of 21-33 has reduced the subset of semcards 21-28 to the three semcard instances of type “triangle” which all contain a “white circle” dimension 21-29, 21-30, 21-32.

- Referring to FIG. 22, the user selects value 22-38, this time reducing the subset of semcards 22-28 to a single semcard of type “triangle” which has
- 20 a semantic dimension of type “white circle” which contains a value of type 22-38.

Because the filter rules are free-standing, it is possible to apply filters to filters, providing a powerful way to program the way certain semcards and their dimensions and values can be filtered in the interface.

Referring to FIGS. 8 and 23, both screenshots from the user interface of the semcard management application the filter panels have two possible layouts: one in which the panels are displayed across the panel as shown in container 804 in FIG. 8. and another in which they are “stacked” or displayed on top of each other as shown in container 2301 of FIG. 23 in a way that only the selected feature labels, 2302, 2303, and 2304, are visible to the user after a selection of the feature has been made. The latter method leads to a visually appealing display and is spatially compact allowing more space for the viewer panel and results panel.

Referring to FIG. 24, each filter container X, Y and Z shows the “stacked” states of the filter panels, corresponding to the same states of the filter panels marked X, Y, and Z in FIGS. 19, 20, and 21, respectively. In the “stacked” version shown in FIG. 23, when a feature has been selected, the filter panel gets “stacked”, and is given a title, such as “Documents” and “Authored By”, that corresponds to the feature that was selected, as will now further be described.

As mentioned, filter rules can have human-readable labels. These can be used in the display to make the features more readable, e.g. instead of a feature list containing flat labels such as the list {semcard: Document, author: Joe, owner: Frank, moderator: Sue}, the list can be embellished with natural language phrasing such as in this example: {a discussion, authored by Joe, owned by Frank, Sue is moderator}, etc. The generation of human-readable labels is managed by a combination of local rules stored with each filter rule, and by a set of global rules that apply to the whole set of filter panels, and

whose job it is to make the path chosen by the user read more like a sentence than a series of nouns and verbs. To take an example, referring to the filter containers X, Y, and Z of FIG. 24, instead of listing the filter path as {a triangle, a white circle dimension, value is a}, the tags could read {a triangle, with a white circle, containing the value 'a'}. This feature becomes especially important in the alternative display of filter panels shown in FIG. 24 where the filter panels are stacked.

The filter mechanism of the semcard system can use one or more ontologies, which can be used for determining which filters are available for any given state. For example, any node above a set of sub-nodes node in the ontology can be considered a “stop flag” node, in the following way. Any dimension which is defined in a sub-node is not displayed per se, but instead its stop flag node, which is higher up in the ontology, is displayed. Referring to FIG. 18, , the white square could be set as the stop flag for the black square, and the white circle could be set as the stop flag for the black circle.

To navigate backwards in a previously chosen path such as that shown in FIG. 21, the user simply selects any feature in any of the displayed filter panels. In the alternative layout in FIG. 24, the user re-selects a prior feature, e.g. the triangle 24-25 in layout Z, to go back to see the features in that panel. The semcard management application also provides forward and backward arrows that allow users to navigate one step (selection) at a time back and forth.

The semcard management application enables users to save a query constructed using the filter panels, as well as other filter sequences or queries

created by any other method, as a named “views” – software objects identified in the interface with a human-readable label or icon. Selecting a view (e.g. by clicking) will run the query again on whatever set of semantic objects it is applied to (i.e. its input), as selected by the user in the interface. Alternatively, a view can be set to update its result set (by running its query) on a periodic basis, or event-driven based on other events such as every time a new semcard is posted, based on standard subscription ~~meehanims~~mechanism, or based on various events in remote semcard collections, such as for example those located with a remote semcard management application elsewhere on the network.

There are at least two ways to represent visually the effect of a selection of such a saved query. One is to display the full set of selected filter panels again, as they looked when the query was built. The other is to hide this path and show only the semcard set resulting from the query in the results panel. The latter may be better if the user wants to further extend the query with other subsequent ~~semanies~~semantic filters; the former is better if he wants to modify any existing part of it. Views can be moved around in the interface as any virtual object such as contexts, and its input can be freely selected, even after it has been created, by, for example, copying a view from one context to another, or using it as an entry point.

It is worth noting that filter panels as described are not dependent on semcards; they can be applied to any set of objects with properties, as is known in the art.

A view can be shared with anyone by representing it with a semcard that is shared with other users in the way semcards are shared, via relationships.

The database component provides data storage for semcards and, can
5 have any type of underlying database. Semcards and ontologies-ontologies are stored, accessed and searched in the database component, as are credentials and encryption keys.

Finally, the semcard management application of the present invention also has Relationship Management capabilities. It allows a semcard
10 application system user to communicate intelligently with other peers executing the semcard application system in a seamless manner. It allows users to share semcards they have created with other peers.

Semcards can represent relationships between people. On a computer-mediated network, semcards can be used to control and automate several
15 aspects of relationship management. In the semcard management application relationships are managed via Relationship semcards. The Relationship semcard stores all information relevant to a relationship, including the parties, their permissions, and the type of automated instructions related to the relationship. The automation component manages the execution and
20 maintenance of relationship-related rules.

A relationship establishes a virtual communications channel between the users. By default, unless a relationship is formed between the users, no communication channel between them exists and thus they cannot directly

interact with one another. (An exception to this is where indirect communication can be achieved via various mechanisms, described below.)

The semcard management application is hard-coded to treat the Relationship semcard with top security. By default the Relationship semcards are non-sharable and non-cacheable except through specially secure protocols.

To the user, the Relationship semcard appears as an ordinary semcard. It has the same interface as other semcards, and can be manipulated in the same way by its owner, containing links to semcards in the semcard space, facilitating navigation, including the people involved, their interaction history, interaction rules, etc.

In creating a relationship, one party, the sender, initiates its creation, by posting a relationship semcard invitation. The Invitation semcard can be made to include a unique address that enables the recipient to reply only this particular invitation, and which can be set to expire after a certain time, as well as based on various events such as the recipient trying to reply in ways which are not allowed by the Invitation semcard's policies.

The receiver has the ability to reply with an acceptance, decline, cancellation, or counter-invite. When they have been posted, semcards representing relationships can be in one or more of the following states, without being limited to this set: (a) Introduction, (b) invitation, (c) accepted or (d) declined, (e) in negotiation, (f) policy change, and (g) terminated. In all cases a reply is returned to the sender with the exception of cancellation. A counter-invitation has the choice of being accepted, declined or cancelled by

the sender (there is no counter-invite to a counter-invite – the next step would be a new offer from the sender). A Relationship semcard can have a pre-built protocol that determines the transition of the semcard between these states, a set of pre-built, single-action reply per state (the equivalent of buttons), as
5 well as an alternative free-form reply, for each state of the relationship creation.

If the recipient opts-out of the relationship, i.e. does not agree with the terms, does not reply to the invitation within its time-to-live (same as manual cancellation), or replies with a rejection, then the relationship will not have
10 been established. The only type of semcard that can be shared in the absence of a mutually-approved consenting relationship is an Invitation semcard.

When a user targets a semcard at another party (using an e-mail address or semcard system ID/alias), for sharing or offers/requests, or alerts, the system first checks to see if the parties have an established relationship. If
15 no relationship exists, the initiating party is first prompted to fill out an Invitation semcard. The Invitation semcard is a transaction/process semcard whose states are specific to starting and negotiating the terms of relationships. The Invitation is delivered to the other party as plain text email with a MIME attachment of the Invitation semcard, as well as an inline URL that links to an
20 on-line hosted HTML version of the Offer semcard. If the recipient has the semcard system, they can use the MIME attachment directly. If they do not have the system, they can either download the application, or a viewer applet, or they can use the on-line HTML version. Through one of these means a receiver views the Invitation semcard to fill out.

Once they have received a relationship Invitation, they fill in their side of it, and then reply via a pre-configured button on the Relationship, which is one of “Accept”, “Counter-invitation”, “Decline” and “Cancel”. If both sender and receiver have the semcard system, the recipient now has the Relationship
5 semcard in their semcard management application. If they do not have the semcard system, they can access the relationship via the hosted on-line account via the included URL, regardless of whether the party has the semcard system. However, this feature may place significant limitations in terms of the number of relationships it supports, how many semcards it can
10 store, as well as and security control.

If a relationship already exists, then the semcard system delivers the semcard according to the optimal combination of (a) relationship preferences of the recipient for how they want to receive it, and (b) the best currently available mode of delivery.

15 Like all semcards, Relationship semcards can be set to have a time to live (TTL), as can invitations and any step of the process of forming a relationship.

In the semcard management application one or more relationships may exists between any two semcard management application users; with any
20 multitude of permissions, instructions and access control that applies to either party that will be stored with their one or more Relationship semcards. For example, if user A has given user B permission to view (and optionally cache on their own system) a set of semcards on A’s system, and A has given a group of users, of which user B is a member, permission to view another set

of semcards on A's system, then user B has access to both sets of semcards on A's system. Relationship semcards can represent any form of current Internet relationships, such as email, instant messaging, ~~disuessiend~~discussion groups, etc.

- 5 By default, relationships are bi-directional. Both parties give each other access to information in their system. Policies and rules are typically agreed upon during the creation of the Relationship. However, policies can be modified by either side any time during the relationship. For such changes, the parties can decide whether the other party is notified of the changes, or gets to
- 10 approve the change. In a bi-directional relationship the initiating party (sender/inviter) always creates an invitation for a relationship.

Relationships can also be uni-directional. In a uni-directional relationship, only one party has access to another's system.

- If one party in a relationship wants to change (increase or decrease) the
- 15 access they have to the other party's system, they can issue a Relationship Modification Request for those changes. The owner of the system in question will then have to accept the request in order for the change to go through. The steps follow the same pattern outlined for creating relationships, with the exception that the new Relationship semcard automatically inherits all policies
- 20 of the previous Relationship semcard, except for those that have been changed.

An on-line semcard application system service provides lookup for all semcard system users to allow them to make direct peer-to-peer relationships for making offers and requests. How the semcard system users discover each

other can be (1) by browsing, if a party has made their contact info available on-line in human-readable and machine-readable formats; (2) by discovery via hosted on-line lookup service, using the name of other party and/or keywords or passwords exchanged between the parties, as well as (3) direct hookup
5 between the computers via exchange of IP addresses.

In a number of cases, a semcard system user may want to make subsets of their semcards available to whoever is interested. This can be done by having a relationship with the public, which is a relationship hosted by an on-line semcard service provider. (This relationship is also the one that users use
10 to allow anyone to post Relationship invitations to them) By setting the policies on the Public Relationship, semcard application system users can open up various parts of their semcard collection to outsiders on a pull-basis, or as the related rules prescribe.

Setting permissions and default policies for relationships can be done
15 via a How tab on the Relationship semcard, as shown in FIG. 25. Looking at the Who tab will bring up information about each member of the relationship, provide an overview of their permissions, and provide links to the specific details of these policies for each member. This enables one quickly to locate the policies for any member of the relationship. For example, if one wanted to
20 change the policies for a particular member, the fastest way to do so may be to go to the Who tab, locate the person alphabetically, look at the list of policies beside their name, and click on the one which needed to be changed; this would instantly bring up the right policy for that person in the How tab. A special section for custom rules holds extensions and shortcuts to the other

rule panels. Rule semcards can be linked into this area for a quicker way to set policies for the relationship. Thus, a user could link the rule semcard for their “friends” relationship directly to a newly created relationship, to have the rules for the new relationship be identical to their “friends”

- 5 ~~relationship. There~~relationship. ~~There~~ are two levels of rules and policies in a relationship. Level one contains the standard permissions as listed in the examples above. Level two concerns rules about the relationship itself – who can change it, cancel it, who can modify its policies after it’s been created, etc.

- Whitelists and blacklists are UI constructs to quickly assign global,
10 top-level rules about sharing for any set of semcards. Furthermore, a whitelist and blacklist can be used in the system to selectively control rules for Relationships. Using a combination of semantic and fuzzy categorization, the system can classify Invitations based on the level of authentication and trustworthiness of their author. Whitelists are a way to set global settings
15 quickly for all members of a relationship on all general dimensions, such as caching permissions, forwarding, duplication, copying, etc.

- Using semcards to hold metadata, policies, and automation instructions about a relationship, combined with a comparison mechanism as described in FIG. 25, users can control in detail: (a) Who can send them what kind of
20 information, (b) Who can search, view, and operate on which semcards and their referents in the user’s ~~possession~~possession, (c) Automation, such as what kinds of events, initiated by people or processes with whom the user has relationships, trigger what kind of automatic system responses, (d) What kinds of services are available on one computer or account for the other party, such

as caching of data, processing and matching, forwarding, (e) What kinds of notification one account should give the other. These rules can be defined hierarchically, to resolve conflicts automatically; general rules about the relationship generally take precedence over rules applying to a single incident
5 of sharing, for example. They can also allow exceptions, by asking the users whether they want to override global rules, when a conflict is detected.

Referring to FIG. 26, computational devices 26-1, 26-2, 26-3, 26-4 are connected via a computer-mediated network 26-6. Each device has a computer-readable storage medium 26-5, 26-7, 26-8, 26-9, on which
10 computer-readable entities and a knowledge base containing semcards is stored. Semcards 26-12 and 26-10 represent relationships. Semcard 26-12, owned by user A, references 26-11 semcard 26-10. Together, 26-12, 26-11, 26-10, represent a uni-directional relationship between owner A of semcard 26-12 and owner B of semcard 26-10, where user A has a uni-directional
15 relationship with user B. To control this, semcard 26-12 references 26-13 semcard 26-14 which contains rules about what kind of semcards and data user A can send to user B. Rules in semcard 26-14 determine the terms of the relationship that 26-12 and 26-10 have, including those described below.

Referring further to FIG. 27, a bi-directional relationship 27-16, 27-20,
20 has been established between user C on device 27-3 and user D on device 27-4. Semcard 27-19 sets the rules (access and sharing policies, display and automation policies) about what data user C can push (post) to user D, and what kind of pull (queries, browsing) user C can do on user D's device; semcard 27-21 sets the same rules about D's access and permissions on C's

device. In other words, semcard 27-19 controls whether user C can send data to user D and whether C can browse or query user D's semcards and data. Semcard 27-21 controls whether user D can send data to C or browse or query against C's data.

- 5 Semcards 27-14, 27-19, 27-21 also hold rules about relationship termination, backup, bandwidth, and other issues that pertain to each relationship, and the actions that can be supported by the system for each party.

- The rules pertaining to push and pull can be replicated for each
10 participant on the owner's peer, such that all users have a copy of the rules they have shared with the party they have a relationship with. In this case, for relationship 27-20, semcard 27-19 would hold push policies for the direction from user C to D, as before, but semcard 27-21 would hold a copy of these rules; rules about pull by D from C would also be stored in semcard 27-19,
15 and a copy would be stored in semcard 27-21. This would then be replicated for the relationship direction 27-16. The benefits of this arrangement is that should user A violate policies on his peer regarding what he is allowed to push to user B, through a malicious act or a failure of the system, user B's peer, now receiving data from A which is not allowed to be sent to B by A, can
20 notify B that user A is in violation of their agreed-upon relationship policies.

Multi-party, or group, relationships can also be supported using semcards. Such group relationships may be established in various ways, including the following way: Individual one-on-one relationship semcard invitations are sent from the inviter to all named parties in the proposed group.

All messages go to the originator of the relationship – no negotiation happens between any two invitees until the originator has gotten an acceptance from both of them. In one variation of this mechanism, parties cannot communicate other types of semcards with one another, until all parties accept the terms of the group, as set by the initiator of the group. Another way of establishing groups is by using a unique ID for the group, to which any semcard can be addressed. The members of the group will then subscribe to the group (via its ID). They can put filtering on the group, such that only particular semcards reach them, as described elsewhere in the present invention.

10 The uni-directional relationship 27-11 has been extended to a bi-directional relationship 27-23, between the owners of semcards 27-12 and 27-10; policies 27-30 have been extended for controlling the relationship 27-23 from 27-7 to 27-6. Further, a bi-directional relationship 27-26, 27-27 has been established, making up a complete bi-directional group relationship between

15 owners of semcards 27-12, 27-15 and 27-17. Alternative implementations of such group relationships, for linearly scaling to large groups, can be achieved by using servers, as described in the literature, and with the benefit of using semcards to represent such relationships. Semcard 27-14 has now been extended with rules pertaining to relationships 27-15 and 27-17; semcard 27-

20 19 has been extended with rules pertaining to relationships 27-10 and 27-12; semcard 27-21 has been extended with rules pertaining to relationship 27-12. Further, a uni-directional relationship 27-28 has been established between relationship semcard 27-17 and 27-10; semcard 27-30 has been extended with rules pertaining to relationship 27-17.

A relationship can also be created by a user for some set of third parties, without including themselves in the group. In one embodiment of this system, the user sends an introduction semcard to two or more third-parties. The third parties establish a relationship according to the methods described
5 above. In one variation, a party may only do this with other parties whom they have already established relationships, unless those parties have explicitly stated in their global relationship policies that they accept such unsolicited relationship invitations.

Relationships and introductions can be accepted or declined manually
10 or automatically. In one embodiment, once established, if either party changes the relationship semcard in any way, relevant parties in the relationship will be notified of the change, at which time they may ignore/accept the change, or they may modify their policies or terminate the relationship if they disagree with the changes.

15 In one embodiment, a user may maintain more than one relationship to another user – for example they may have one relationship for “personal communications” and another for “business communications” with the same party, each with different policies, identities and addresses. In such a case, a user might terminate one of these relationships, but would still be able to
20 interact with the other party via the remaining relationship, according to its policies, etc.

When creating a relationship, a user can choose which of their rules are visible to the other party, and which are hidden. Further, the user can decide if the hidden parts of the relationship are exported to the other party’s

peer or not. If they're not exported, they are more secure from unwanted exposure to the outside. However, since they can only be enforced on the owner's semcard management application peer, this means that the flow of data from the other party cannot be controlled at the source on their peer.

- 5 A user establishes relationships with other users by exchanging offers and requests for relationship Invitations semcard among user accounts. A relationship Invitation is a semcard that contains choices for responding to the invitation that encode acceptance or rejection of the proposed relationship. Only when both users to a potential relationship mutually accept relationship
- 10 Invitations to one another is the relationship initiated. If the receiving party does not have the semcard peer application, the Invitation goes via regular email to them as either an HTML form, or a URL that points to a Web page where they can choose to accept or decline the invitation. ~~Even invitation. Even~~ when users have no relationship they may, however, be able to interact and
- 15 share indirectly with one another via relationships they have to other uses and sequences of relationships that connect them indirectly. Once they have a direct or indirect relationship, users may then route and match offers and requests for information to one another, browse and query each other's semcards, according to access policies.
- 20 When users have a relationship they can exchange semcards of various types that serve the purpose of communication between the parties. For example, a user can fill out a semcard called "note" and address it to a party with which they have a relationship, replicating the functionalities of email, but with the full benefits that semcards, Relationship semcards, and the

semcard management application provide. Further, users may specify the mechanism by which the recipient of such communication should be notified – whether by a pop-up message, a “flag”, sound, or by other means. They can also specify the urgency of such notification, such that the recipient’s semcard management application can apply rules as to how best to notify the recipient of the communication. Policies of the sender will specify (a) the preferred default way of notifying the other party of communicative actions (and, in fact, of any sharing event or other communicative event on the relationship), and (b) what the rules are for various urgency levels selected for such events.

10 The recipient may have specific rules for the relationship about what kind of events thus specified by the sender are allowed to be followed on their side. This is mirrored for any interaction in the other direction. Global rules may also be set for all relationships, or specific groups of ~~relationships~~relationships.

An ~~extension~~extension of this design relates to instant messaging between the two parties. Rules about when each can be accessed, when they are listed as being “available” for chatting, etc., can both be set per relationship as well as globally for groups of ~~relationships~~relationships or all relationships.

15

The system of the present invention is capable of intelligent matching of offers and requests, involving all types of knowledge: Information, ideas, suggestions, opinions, products, services, jobs, events, people, skills, etc, using semcards and semcard-like structures, creating a bi-directional marketplace on the Internet. The invention enables parties to search and do marketing in the same way, in the same environment. This reduces the

20

complexity of finding matches to offers and requests, which often involves both searching for others and marketing so that others can search for you. The system also helps providers search for seekers who want what they offer and enables “reverse search”, a bi-directional network is created, doubling the utility of the uni-directional nature of the Internet for these purposes, as described earlier.

Semcards, and knowledge networks, can be designated as being offers or requests on a computer network, for various purposes, including (a) advertising, (b) offering of merchandise, or (c) finding or procuring items. This can be done in at least four different ways: If a single semcard is being offered/requested, metatags in the offered/requested semcard contains the offer/request metadata. If a single semcard or a knowledge network is being offered/requested, a separate semcard can hold the offer/request metadata. In the latter case, the separate semcard can either wrap the offered/requested semcard or knowledge network, or refer to the semcard or knowledge network using one or more reference pointers.

Offers and requests are thus semcards or similar-structured software objects, comprised of meta-data that defines the attributes of the particulars regarding the offers and requests they represent, and where the payload describes what is offered or requested, such as jobs, resumes, opportunities, products, services, etc. Users can manually create offers and requests for things using the system user interface. In particular this can be useful when representing things that have no electronic substance, such as ideas or things that are not represented by documents or files on a computer.

Parties create forms by selecting the appropriate form templates from a directory of alternative form templates for various purposes and then fill out the relevant parts of the semcard, optionally linking them to other semcards and/or target reference, and post them to the network. There are at least two

5 types of addressing a semcard that enable both “direct” and “indirect” targeting or routing, for purposes of sharing, or offers, requests, invitations, and other types of targeted – or goal-directed – semcards. With direct targeting a semcard is sent to explicitly named recipients with which the semcard’s author has an existing relationship. With indirect targeting, on the

10 other hand, a semcard is sent to recipients who satisfy various criteria. An offer or request can be targeted to selected parties, loosely-defined on-line groups of users, or to public forums. These targeted recipients can be defined in a fuzzy manner, using a matching engine to determine the level of relevance of the offer/request to any party encountered, using matching

15 mechanisms described below. Indirect targeting is useful for reaching unknown parties who are interested in a particular topic. Using these methods, the target audience can be defined as specifically or generally as desired by the sender.

When the semcard has been specified to the user’s satisfaction it can

20 be test-posted. Test-posting provides an estimate of how many matches may occur, how much the posting may cost, etc. The user may then tune the semcard’s goals policies to refine it based on this estimate before posting it. Users may repeatedly refine and test-post until they are satisfied.

Another more advanced option is to have an on-line service evolve an optimal semcard or set of semcards for a particular campaign. In this mode, the user provides some example semcards that represent their goals and the on-line service will use various algorithms to evolve and repeatedly test-post
5 generations of similar semcards to arrive at a semcard specification that has optimal price-performance attributes. This semcard can then be posted by the user.

When an offer or request has been posted, it is routed over the network in various ways, depending on what kind of semcard it is. Using semantic
10 routing, for example, semcards that represent offers, requests, and queries, can be routed semantically between nodes on the network. Using peer-to-peer routing, direct relationships can be leveraged to send sharing policies, notifications, alerts, and messages.

Referring to FIG. 28, computational devices 28-1, 28-2, 28-3, 28-4,
15 28-5 are connected via a computer network 28-6. Each device has a computer readable medium, on ~~which~~which semcards are stored 28-7, 28-8, 28-9, 28-10, 28-11. A semcard 28-11 is used to produce 28-13 a routing profile 28-14. The routing profile describes salient features of the semcard, as detailed as deemed necessary for supporting efficient routing of semcards. The routing profile 28-
20 14 is propagated to other computers on the network 28-2, 28-3, 28-4, and stored on their computer-manipulatable storage media 28-8, 28-9, 28-10.

The profile does not necessarily point directly to the original home semcard from which the routing profile was generated; a copy 28-19 of the

original routing profile 28-14 may point 28-20 to the node 28-9 from which it received the routing profile, as described in the art.

The routing profiles 28-15, 28-17, 28-19 serve as pointers 28-16, 28-18, 28-20 in the direction of the node 28-1, 28-7 that hosts the semcard 28-12
5 from which the original profile 28-14 was generated. If the original semcard 28-12 represented an offer for something, the routing profile will also represent this fact, and specify that it can match to requests for its metadata. When user of computing device 28-5 creates a semcard 28-21 that represents a request containing metadata that matches the original semcard 28-12, a
10 request semcard will be routed 28-22 to the nearest node 28-4, 28-10 on the network. If the receiving node 28-4, 28-10, contains a routing profile that matches the semcard's 28-21, it will route it to the node 28-9 to which the routing profile 28-19 points 28-20.

Semcards can be routed using the same principle in a network with
15 dedicated routers. Referring to FIG. 29, computational devices 29-1, 29-2, 29-3, 29-4, 29-5 are connected via a computer network 29-6. Each device has a computer readable medium 29-7, 29-8, 29-9, 29-10, 29-11, on which
semcards are stored. A semcard 29-12 from which is produced 29-13 a routing profile 29-14. The routing profile is propagated 29-27, 29-28, 29-29 to the
20 routers on the network 29-24, 29-25, 29-26. In the same manner as before, a copy of the semcard which is posted/published onto the network travels on the network 29-33 to the nearest router 29-26, at which point the router forwards the semcard to the closest router, and so on, until it arrives at the node 29-1, 29-7 where it was requested.

As explained in the art, two or more routing profiles can be aggregated and compressed, to represent thousands of them in a single table. A routing table is an aggregation of two or more routing profiles, degraded in specificity based on the distance to the home knowledge base whose data it represents.

5 This can also be done with semcard routing profiles. Each routing table would contain partially aggregated and partially or fully compressed interest profile of downstream semcards. Semcards representing offers and requests are passed on by routers to nearby routers that have relevant interests, in a decentralized manner, until they reach edge-nodes where their content has

10 been requested or is needed.

Routing tables can be propagated via semcard relationships, as can published offers and requests which are routed based on the routing tables.

When semcards have been routed to a recipient node or semcard deemed worthy of matching against, matching processes such as agents,

15 scripts or programs, can compare pairs of semcards to determine the level of match between them. Such processes work continuously on behalf of seekers and providers, enabling them to go off and work on other things until matches are found. The system understands the meaning of offers and requests and eliminates irrelevant search results by semantically matching them to each

20 other.. If seekers wants to find “rock,” they can directly tell the system whether they mean “rock music” or “rocks and minerals,” which the system subsequently understands and can make use of.

Semcards can be compared on their slots, both semantic dimensions and values. Such comparison can be used for various purposes, including (a)

routing, (b) matching, (c) one-of searching/querying/browsing, (d) standing offers/requests, (e) filtering, and (f) inferencing.

- Referring to FIG. 30, semcard 30-1 composed of four parts 30-2, 30-3, 30-4, 30-5, each segment containing a set of meta-tags and meta-data, and
- 5 another semcard 30-6 composed of four parts 30-7, 30-8, 30-9, 30-10, the parts being for example a basic specification, a display specification, a policy specification, and an automation specification, each containing metatags and meta-data 30-12, 30-14, 30-16, 30-18 in semcard 30-6 and 30-11, 30-13, 30-15, 30-17 in semcard 30-1. The size or complexity of a semcard can vary.
- 10 Comparison between two or more semcards can proceed in two steps, the first step comparing their metatags, and a second step comparing their metadata.

- Referring to FIG. 31, shown are the meta-tags 31-20 of a first semcard and the meta-tags 31-21 of a second semcard, compared or matched in a comparison module 31-19, using a plurality of comparison algorithms 31-22,
- 15 providing an output 31-23 of the similarity between the meta-tags of the two semcards. The second step, comprising metadata 31-25 of the first semcard and the corresponding metadata 31-26 of the second semcard, and a comparison of these in a comparison module 31-24, using a plurality of comparison algorithms 31-27, provides an output 31-28 of the similarity
- 20 between the metadata of two semcards. The output 31-23 of the first comparison module 31-19 provides a separate result for each meta-tag, and enables the next step in comparison module 31-24 to be done more intelligently.

An offer, request or other semcard which is designated to be matched to other compatible semcards, has associated policies which determine how the matching should be done. In one alternative, only metadata whose metatags are identical between the compared semcards, are compared in the

5 second step. In another alternative, a continuous measure of distance (difference) is used, in combination with a threshold, is used to determine if metadata for each metatag should be compared; if the distance metric is larger than the threshold, the metadata for that metatag is not compared. Both metatags and meta-data can be compared using an ontology, if they are defined

10 using one. However, even if only meta-tags, or neither meta-tags nor meta-data, are defined using an ontology, comparison can still be performed, using different methods, which include string comparison, synonym comparison, or other such comparison mechanisms as described in the art.

Matching or comparing a collection of semcards, i.e. a knowledge

15 network, is an extension of the above principles. In its simplest form, each object in the collection is compared to each object in the other collection, and the number of exact matches is counted and used as a direct measure of similarity. A more advanced embodiment of this includes using e.g. an ontology or taxonomy to generalize the type of object, for example, if an

20 object of type dog is compared to an object called animal, and their relationship can be determined by the use of one or more ontologies, or by some other means, the similarity measure does not simply mark them as dissimilar, but calculates a measure that represents the distance between the two objects and their meta-tags and meta-data. Even though the semcard of

type animal may be different from the one of type dog in many ways, dog is a subtype of animal, and thus will have more similarities than a dog and a table. Another embodiment could ignore the type ~~altogether~~altogether and compare a dog and a table semcard by first comparing their semantic dimensions, both of which may contain the meta-tag “number-of-legs”, which may contain the value four. In this scheme, the similarity between a millipede and a table may be judged to be less than the similarity between a dog and a table, if “number-of-legs” is one of a few semantic dimensions being compared, because both a dog and a table have four legs.

Knowledge networks that is offered can be represented by a collection of Offer semcards, a single Offer semcard, or a compound hierarchy of Offer semcards, where the network is described at various levels. In this last case the matching algorithms “know” about the network’s structure, and can match intelligently to requests for various parts of the network as well as the whole network.

Typically, offers are matched to requests and requests are matched to offers. It is also possible to offer requests, and request offers, making it possible to distribute collections of such semcards in one go. In a routing network, whether peer-to-peer, client-server, semantic, other type of network, or some hybrid, a suberiptionsubscription is represented as (a stationary) routing table entry that typically lives on a particular server; a publication is routed in the network – i.e. it travels to wherever there are stationary relevant subscriptions. An offer or request can be posted either as a subscription, a publication, or both. The decision as to which of these is used for any instance

of a posted semcard can be made based, among other criteria, on (a) relative frequency of offers vs. requests, (b) network bandwidth, (c) computing power of the computational devices on the network, etc., and it can be made dynamically and automatically by the system based on various states of the network at different times, or hard-wired into the network and routing mechanisms.

There are thus three different matching combinations for published and subscribed offers and requests: (a) published offer and subscribed request, (c) published request and subscribed offer, (c) a combination of options (a) and (b). The first represents the traditional situation where people are matched up if one of them has something to offer and one has something to request, where requests are stationary subscriptions and offers are published onto the network. Option (b) is the inverse equivalent of (a). For any network, a decision has to be made whether either options (a) or (b) are hard-wired into the network design. The subscription is typically offers more security because the semcard itself is only propagated anonymously into the routing tables, so the choice of this option may actually also be left to the user. In such a system offers and requests can be either publications or subscriptions. Of course, should the user choose to post an offer as a subscription in such a network, the user will only get matches on requests that are publications, hence reducing the potential number of resulting matches. Alternatively, option “c” makes it possible to choose both. The choice as to the network design can be made based on several criteria, including but not limited to (a) security requirements

of the network, (b) available bandwidth (network and computing power), and
(c) desired simplicity (doing both is more complex).

Once matches are found, various further activities may then take place according to the specifications of the matched users or parties. For example,
5 one or both users may be notified or they may receive the matching form, or manual or automated activities may take place to transfer files, buy or sell things, reply to one another, forward messages to other parties, launch external applications, etc. These further “follow-up” activities can be manually initiated and completed by users, or they can be automated by
10 software agents, scripts or programs attached to user accounts and/or to particular relationships, offers or requests. The system’s automation processes can follow up on tasks, according to the rules specified for the offer or request by their authors, allowing automatic ~~processess~~processes to respond, issue alerts and notifications, transfer files, make or accept payments, etc., on their
15 behalf. The automation processes can also help the matched parties communicate by facilitating anonymous or authenticated interactions.

Identity or the authenticated person in the semcard is typically stored as either encrypted or non-encrypted data. The identity section in a semcard has four parts:

- 20
1. The author of the semcard
 2. Recipients of the semcard
 3. Parties who have rated the semcard
 4. Parties who have annotated the semcard

If the semcard is an offer or request, this information is added:

5. Parties that have matched and have been notified about the semcard

Each of these can be hidden or revealed based on the semcard policies as shown below.

```
5      SEMCARD
      Goal:
          * Offer
          * Request
10         * Alert
          * Invitation
          * Other
      If offer or request, match to:
          * Other offers of type [default: same as this]
          * Other requests of type [default: same as this]
15     Security level: [high] [medium] [low] [custom]
          Encrypted:
              * Yes [how] [level]
              * No
          Escrow:
20             * Yes
              * No
      Network transport:
          * Subscription (stays on node)
          * Offer (travels on network)
25         * Both
      Notification:
          * Sender
          * Recipient
          * Both
30         * Either
          * Neither
      Authentication:
          * Sender
          * Recipient
35         * Both
          * Neither
          * Either
      Anonymity
40         * Sender
          * Recipient
          * Both
          * Neither
          * Either
```

45 As mentioned above, the decision about when and how to contact two parties of a matching offer and request is based on the rules and policies of the two semcards. Rules can be specified for every part of the process. The rules also dictate the matching process. For example, rules may include how exact or fuzzy the matching should be for each field, field priorities, which fields
50 are required to be matched for notification to occur, how notification should

be handled, what kind of user authentication is required for a match to occur, how the semcard author's identity should be hidden or revealed to matched parties, etc. Available policies include:

- Notification
- 5 ▪ Matching
- Payment terms and policies
- Sponsorship terms and policies
- Identity
- Privacy
- 10 ▪ Certification or Authentication
- Security policies
- Reply policies
- Browsability
- Receipts
- 15 ▪ Payment terms and conditions
- Billing terms and conditions

A price can be attached to the launching of a semcard; the price represents a function of the system-cost in routing and matching the semcard.

- 20 Depending on the particular service, this price may be passed on to users by requiring cash payments, or it may be absorbed or subsidized by the provider or advertisers, etc.

- If users cannot find a semcard template that suits their needs for describing what they want to represent, they can extend the templates already
- 25 provided, or create new ones that inherit from the ontology defining the current templates. They can subsequently submit such extensions to local semcard-capable servers, or to a central semcard ontology repository. Such

central repositories keep track of the most popular forms for describing various things in the world with semcards. Such repositories can provide semcard management application users with a list of the most popular semcards for representing various concepts in the world. The statistics are

5 received by virtue of linking to other such servers, such servers keeping track of the number of people submitting various types of semcards. (Semcard similarity is computed using a matching engine, as described above.) The consolidation feature enables the system (or the end-user) to take all the fields from all the various alternative templates for a node and rank them in terms of

10 (a) the number of active postings in the system that use such a field, or (b) the number of active opposite postings (if the post is an offer, then the opposite postings are requests) that seek that field). Then the system creates a consolidated form containing all the most important fields from all the best alternative forms for that node (e.g. Job Offer), but ranked in terms of

15 popularity. Thus the first dozen or so fields are probably the most widely used by users of the system. This enables a user to fill out the consolidated form instead of just one particular form, choosing the most popular fields to fill out from among all the fields being used in all alternative form templates for the node, and this will give them maximal compatibility and reach. Once users

20 have created new semcard templates, or extended the ontology, they can share such extensions with each other using semcards representing semcard templates and ontology branches or whole ontologies.

The marketplace system of the present invention makes matching more efficient by enabling seekers and providers to cooperate in finding one

another, under a unified framework that fits into the semcard management application and the semcard framework (but can also be implemented separately through alternative solutions). By sharing the work, both parties (and the computers of both parties) can share the workload for the necessary
5 ~~transaction~~transactions, making ~~interactions~~interactions more balanced. This fundamental process can improve a variety of processes, including:

- Team & enterprise portals
- Search
- Classified advertising
- 10 Permission-based direct marketing
- Personalized content distribution
- Personalized commerce and shopping
- Online marketplaces
- Industry exchanges
- 15 Knowledge management
- Procurement
- Supply-chain integration
- Customer relationship management (CRM)
- Communities-of-interest
- 20 Communities-of-practice

In the context of marketplaces, there are several features that make the marketplace more powerful, as will now be described. These features may also be used in other circumstances besides marketplaces.

The semcard management application provides a mechanism for rating
25 the quality and reputation of content in the semcard management application network and any knowledge network. Every semcard , Relationship semcard, as well as every group relationship, community relationship, and persona semcards, may have ratings associated with it. This enables collaborative filtering, networks of trust, and reputation filtering to take place on the
30 network.

Any semcard management application can have one or more accounts, each one owned by a particular individual or group; each account can have several ~~serveral~~ “personas” – templates that dictate the terms of relationships that its user has with others. The user of an account with multiple personas
5 can be given a rating that is a function of the ratings of all its personas as given to it by those with whom he has relationships, or the cumulated ratings given by others of all its posted semcards. Since the ratings of person A by person B is owned by person B, person A has no control over the rating. The same holds for ratings of semcards: A rating by person A of semcard C, where
10 semcard C is owned by person A, is not ~~modifiable~~modifiable by person A. Since all semcards have a unique ID, and all users are represented by persona semcards, this creates a system where communities of users can use ratings to control rogue individuals in the network.

A further ~~extension~~extension of the utility of this mechanism is
15 provided where a person is represented by their account, allowing the cumulated ratings of their Persona semcards to be reflected back on the account itself, and thus their actual identity, providing a community a further mechanism to suppress unwanted behavior on the network.

A posting receives a starting rating that is a function of the rating of its
20 Persona designated as the semcard’s author. Any rating given is affected by the rating of the rater — this way people with higher rating have a larger say than people with lower/worse ratings on the network. The longer an account has been active on the network the more a new persona created by the account owner will inherit the account’s rating from the start. This will benefit those

that have an account with a high rating and discourage those whose account has a low rating.

A user can rate any semcard and relationship along several dimensions. This includes:

- 5 1) Match quality – was the match a good one? Is the matched semcard useful for what it sets out to do?
- 2) Usefulness – how sensible is the match in the user’s given context?
- 3) Appropriateness of language
- 4) Quality of matched semcard – how well/appropriately was it
- 10 specified?
- 5) Endorsements, with annotation

- A semcard/ontology designer can also add custom rating fields to a matching pair of semcard types. A taxonomy of standard rating scales in the system would be provided, however, users and communities can create their
- 15 own additional custom ratings.

These ratings enter into the overall rating of a matched pair of semcards, as well as its posting party, and the account (persona) of the posting party. When viewing or interacting with a semcard, parties and users can take these ratings into account.

- 20 Parties can also rate their experience with other users, including how satisfied they are with follow-up, if the matched parties have corresponded. Typically users will fill this in if they are not satisfied or have a complaint.

Each party that rates can add a free-text comment. Their ratings for the post, as well as their current persona ratings and statistics about their general

rating pattern, are summarized at the header of their comment. The receiving party is allowed to reply and they can debate in a thread if they wish. This provides some checks and balances to ratings. There is a policy for acceptable conduct in comments. If that policy is violated, such as use of profane language, comments will be deleted and the violator will be penalizedonpenalized on their persona ratings.

Forwarding is a function of the semcard management application, where an owner posts a semcard to another user that he himself received from someone else. In direct manual forwarding semcard is forwarded manually, with no new policies. Semcards can be forwarded from one recipient to another, either directly or indirectly, as described below in addressing methods, as well as manually or automatically. Automatic forwarding means that the account has forwarding rules that posts particular semcards to other recipients; manual forwarding means this is done manually for each semcard.

When a semcard is forwarded it is wrapped in a second semcard which contains additional information, such as who forwarded, their rating, reasons for forwarding, rules (if forwarded by rules), etc. The forwarding party may mask some original links and references with intermediate links and references, only to be traced back via the forwarding party, potentially being subject to policies set by the forwarding party.

Another mechanism is semcard brokering. In the case of brokered semcards the originator of a semcard is not visible to the ultimate receiving party with whom there is a match; the brokering party acts as a middleman for interactions resulting from a match between two semcards. To take an

example, when two users receive a notification that their semcards matched, they cannot reply directly to ~~each other~~each other, rather, they reply to the brokering party, who in turn relays their replies to each other.

The broker can set policies that restrict ensuing activity. For example, she may opt to be cc'd on all subsequent communications between the brokered parties, and she may opt to have all communications between the parties go through her, with or without moderation. She can also restrict the types of matching that can occur, and the types of follow-up that are allowed.

In brokered situations, semcards inherit the rating of the brokering post. This way, semcards inherit any ratings from bad brokers, which allows agencies to create filters that block semcards and/or agencies with bad ratings. semcard brokering has features to manage accountability, trace referral history, and transfer funds related to the referrals and resulting matches.

Brokering differs from forwarding in that forwarding cuts the forwarding party out of any subsequent transactions related to that semcard; brokering obligates the receiver to follow policies that the forwarding party sets on the forwarded semcard. Also, in brokering mode, the broker may benefit from any payment policies in the semcard. Semcard brokering, in ~~contrast~~contrast to forwarding, has features to manage accountability, trace referral history, and transfer funds related to the referrals and resulting matches.

For example, a user may see or receive a job offer and wish to refer it to a friend who is looking for work. The receiving party may do whatever they want with the semcard: match it, respond to it, delete it, and store it.

There are several ways to advertise in a network of semcard management applications. The simplest way is to fill out an Offer semcard of type "advertisement" and post it to anyone who wants to get it that matches the targeting and policies of the advertisement. Another way is to embed or
5 attach an ad semcard to another semcard, so that the ad semcard always travels with it. However, the semcard management application provides two other, ways of advertising using the idea of an "ad stream".

An ad stream provider can publish a semcard of type "Advertising Stream Offer" to content providers who subscribe to the ad stream. The ad
10 stream ~~semcard contains~~ semcard contains meta-data about the content of the ad stream, i.e., the type of ad, the intended audience, how long the stream will run and/or how many ads and impressions per ad are allocated to it, and what will be paid for each impression and each click to parties who run the stream.

Content providers can subscribe for appropriate potential ad streams to
15 run in their sites. Content providers who match may then reply to the ad stream publisher with an application to receive the ad stream. The publisher can reply to the content providers with a custom URL for them to run on their ad slot of their Web site. The URL includes an encrypted ID for the stream and an ID for the content provider. The content provider then runs the URL in
20 its site's ad slots.

Visitors to the content provider's sites cause an ad to be pulled from that URL (which refers to the ad stream provider's ad server). Their ad server sees the ID of the semcard the ad stream came from and the ID of the site that pulled it and awards points to that site's account via the semcard management

application to compensate them for running the ad stream. Subscriptions to certain types of semcards also create subscriptions to certain classes of ad streams. In other words, the targeting that is used to define a subscription is valuable for also targeting relevant ads to that subscriber.

5 For instance, a subscriber has a subscription to get offers for sports cars. When they make the subscription, it also automatically makes a subscription for ad streams that are targeted to people interested in sports cars. Certain classes of offers and requests contain slots for running ads in the content of the envelope when it is displayed to the user. (In other words, they
10 contain a slot for a URL that pulls from an ad stream.) To take a specific example, when envelopes with sports car offers are matched to the sports car subscription for that account, advertisements are automatically added to them depending on how they are being viewed:

1) If the sports car offer semcard is being viewed as HTML, an ad
15 stream URL is inserted into the ad slot in the content. This causes the appropriate ad to be pulled from the ad stream provider and run in the content.

2) If the sports car offer semcard is being sent out to a fax machine, or to SMS, etc., the system either puts a TIFF image of the ad into the TIFF being faxed out, or it puts a text version of the ad into the SMS message, etc.

20 Thus, the particular ad and the format of the ad are not decided until the ad is received and/or displayed by a subscriber.

Furthermore, it is also possible to run ads on email and other types of messages. These ads subsidize the price of sending the messages. If users do not want ads on their messages, they can spend points to buy the ad space.

Ad-free viewing can be paid up-front by the sender of a message or by the receiving party (if either one pays for no ads, the other does not have to pay, even though their settings are set up to filter out ads.)

Users of the semcard network can also buy ad space, either from a
5 local node owner (or from the owner of a central node in the network) and run their own ads in it. To profit they have to charge their advertisers more than they paid for the ad space, creating a marketplace for ad space. So, for example, an advertiser buys the ad space on a message semcard that he is sending out to 100 people who are interested in motorcycles. He pays ten
10 cents up front for the ad space on those messages. He resells the ad space to a third party for (\$.003/impression) grossing him 30 cents, and thus a net profit of 20 cents.

The semcards' unique ID allows the system to track each semcard as it travels on the network. Network nodes or semcard management applications
15 can thus be automatically mined for top trends, topics, articles, resources, etc., which can also be encapsulated as knowledge in semcard and published back to users or central service.

The semcard management application provides an API for useful real-time information about semcard activity in the network. All calculations are
20 based on raw data from the system events:

1. Posting a semcard
2. Receiving a semcard
3. Storing a semcard
4. Matching semcards
- 25 5. Splitting a semcard
6. Combining a semcard
7. Transmitting (routing) a semcard

8. Delaying the transmission of a semcard
9. Delaying transmission of parts of a semcard
10. Reliability of nodes
11. Efficiency of nodes
- 5 12. Displaying a semcard (e.g. browsable, or visible)
13. Ratings of a semcard or user account

In addition, statistics about the following (and more) can be recorded:

- 10 1. the type of semcards received and posted
2. semcards encapsulated in routing tables
3. semcards' slots (their number and types)
4. amount of content per slot (in bytes)
- 15 5. semcard owners (information stored in the semcard)
6. receivers (users who have been notified of matches)

The system can also provide statistics on higher-level phenomena like supply and demand trends for particular types of offers, requests and semcards, number of users with a particular interest profiles, number of

20 potential matches for particular advertisements, and distribution of the user population along multiple dimensions. One method to achieve this last-mentioned option is to create a semcard describing the prototypical condition (average) for a particular trait. The marketing tool would generate multiple variations on this semcard using knowledge-based, iterative test-posts. The

25 resulting semcard population would then provide actual statistics through multiple (hundreds, possibly thousands) of resulting matches, whose distribution describes the “semcard landscape” about the ~~subset~~subset of the network that the semcards would be targeted to when posted.

Standard information calculated includes aggregated statistics for all of

30 these, e.g. total number of network matches for a given duration, where they

occurred, as well as time-dynamics, demographic distributions, popularity ratings, response rates, etc.

In addition to bar charts, pie charts, tables and graphs, the semcard system provides users options to visualize the path and dynamics of a user's semcard plotting their path in concept space, demographic space, or geographic space, and ranking their popularity compared to other semcards in the network. This ranking assists other users in discovering particularly relevant semcards and helps those semcards reach larger audiences. Statistics for the whole network, any node, or sets thereof, can also be viewed in the system, depending on the node's access privileges. Statistics for many of the accounts, agencies and persons on the network can be browsed and searched via the semcard system. This is useful for community accounts, which may advertise their membership policies, member statistics and other information about their existence via semcards that can be browsed. It is also an important source of information for companies, enabling them to visualize what the employees are doing on their computers at the task and event-level – both providing a highly detailed resolution and high level of accuracy about what is actually happening. The high resolution of events and task recording afforded by the semcards enables one to see an accurate depiction of a whole organization at a glance, and then to “zoom in” to areas of interest, to the level of a division, a team, and all the way down to the level of an individual. This can be done both in time as well as in a large number of semantic dimensions.

The following is an example of how the present invention may be used.

1. Sue opens her semcard peer node application and logs in to her business account.
2. Sue opens a word processor and creates a text document called, **"Marketing Plan"**.
- 5 3. Sue creates a semcard for the **"Marketing Plan"** document. She profiles it so that it can be seen by Phil, Lisa, and Dave, as well as by anyone in the "Marketing Team" group. Sue sets the semcard to include a copy of the "Marketing Plan" document rather than just a link to it.
- 10 4. Sue does some market research on the Web and finds two useful Web sites: **"Industry Stats Central,"** and **"Industry Report"**. The system automatically creates a Web Site semcard for each one.
- 5 6. Sue browses her local semcard space for "biotechnology market research" semcards. The results are 60 matching semcards.
- 15 6. Sue selects semcards for two more documents, **"Biotech Industry Report,"** and **"Biotech Industry Market Projections,"** from the search results and uses these semcards to create a new Collection semcard called, **"Biotech Market Research"** that includes them both. She then links the semcards "Industry Stats Central" and "Industry Report" to it as well.
- 20 7. The semcards in a collection inherit a link to that Collection, so from any semcard, Sue can see what, if any, Collections it is in and navigate to those collections to see what other items are related to it and then navigate to them.
- 25 8. Sue creates a Topic semcard called **"Market Research"** and links this Topic semcard to other existing Topic semcards for **"Marketing,"** **"Advertising,"** **"Strategy,"** **"Research,"** **"Project X,"** and **"Product Development."** Each of these Topics now has a link to the "Market Research" Topic semcard as well. Sue can navigate around the resulting semcard map in various ways, by browsing, filtering, querying, and visualizing
- 30 9. Sue adds the "Market Research" Topic semcard to the "Biotech Market Research" Collection semcard. All of the semcards in the collection are now linked to this Topic. The Topic also is linked to the items in this collection. Now from the Market Research Topic semcard Sue can find related documents and topics, and vice-versa.
- 35 10. Sue creates a Collection semcard called **"Biotech Marketing Resources"** and includes the semcards for "Marketing Plan," "Biotech Market Research" Collection semcard.
- 40 11. Sue searches for Web Sites related to Biotech Market Research and finds "Industry Stats Central" and "Industry Report." She can see their metadata including their relations to other Semcards. She can navigate around her knowledge this way.
- 45 12. Sue wants to send the "Biotech Marketing Resources" semcard to her teammate, Phil. Sue uses the "Sharing" command on her client to allow Phil to access it.

13. Phil gets is notified, in his semcard peer application or in his email,
that he has access to a new semcard from Sue called "Biotech
Marketing Resources." Phil now has access to all the semcards that are
linked to from that semcard, including any files that its semcards
5 included.
14. Phil now searches his knowledge store for "Biotech Market Data" and
finds 25 semcards. He links these 25 semcards to "Biotech Marketing
Resources."
15. Phil shares his new links to the Biotech Marketing Resources semcard
with Sue. He attaches also a note explaining what these new semcards
10 are about.
16. Sue sees in her client that Phil has made links to her semcard and
shared the with her.
17. Sue now shares her "Biotech Marketing Resources" semcard to
anyone in the company who requests such resources, including Phil's
15 newly linked semcards. The semcard is routed to the company's
semcard server node, where it resides and is automatically queried and
delivered to anyone in the company.
18. Sue now makes a Request semcard for "Market Research Consulting
Services." She fills out the Service semcard, and posts it to selected
20 departments within in the company. The Request semcard is routed to
the corporate semcard server node. Sue receives matches to it as Offer
semcards. She can then correspond with the matched parties, negotiate,
share further semcards, schedule meetings or live web conferences,
25 and hire a consultant etc.

Although the foregoing invention has been described in some detail for
purposes of clarity of understanding, it will be apparent that certain changes
30 and modifications may be practiced within the scope of the appended claims.
Furthermore, it should be noted that there are alternative ways of
implementing both the process and apparatus of the present invention. For
example, an application that doesn't use ontologies to define concepts can
~~nonetheless~~ implement most of the features described in this
35 disclosure. Applications focusing on particular vertical domains and markets,
such as medicine, crime fighting, law, research, design, etc., can be built with
specialized semcards, using subsets of features described here or obvious but

domain-specific extensions to these. Furthermore, the semcard management application as described can be adopted to handle other semantically-rich entities besides semcards and others of those listed here. Accordingly, the present embodiments are to be considered as illustrative and not restrictive,
5 and the invention is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

CLAIMS

What we claim is:

- 5 1. A method of matching an offer semantic object and a request semantic object, the method comprising:
 - creating an offer semantic object and a request semantic object by
 - completing semantic object templates; and
 - storing specific data of a request in the request semantic object and specific
- 10 data of an offer in the offer semantic object;
 - wherein each semantic object is routed in a network and contains policies
 - that determine how each semantic object should be matched.

ABSTRACT OF THE DISCLOSURE

5 A Among other disclosure, a knowledge network and semcards
enabling intelligent matching of offers and requests, involving all types of
information and knowledge, including information such as classified ads, data
about products and services, or knowledge, expertise, ideas, suggestions,
opinions, and other forms of tacit knowledge is described. The invention is
capable of intelligent matching of offers and requests, involving all types of
10 knowledge: information, ideas, suggestions, opinions, products, services, jobs,
events, people, skills, etc., using semcards and semcard-like structures,
creating a bi-directional marketplace on the Internet, desktop or intranet. The
invention enables parties to search and do marketing in the same way, in the
same environment.

15 A semcard can be designated as an offer or a request. When the
semcard has been specified to the user's satisfaction it can be test-posted.
Using semantic routing, semcards that represent offers, requests, and queries,
can be routed semantically between nodes on the network. The routing profile
describes salient features of the semcard, as deemed necessary for supporting
20 efficient routing of semcards. Collections of semcards can also be matched or
compared in a knowledge network. Users can also create new semcard
templates or extend the ontology, and share these extensions with other users
in the network.

In another aspect of the invention, the semcard management
25 application provides statistics on phenomena such as supply and demand
trends for particular types of offers, requests and semcards, number of users
with a particular interest profiles, number of potential matches for particular
advertisements, and distribution of the user population along multiple
dimensions.

30




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 24




Fig. 26




Fig. 27




Fig. 28




Fig. 29





Fig. 30




Fig. 31